



Product: [0905 203 302](#) 

DeviceNet Power Supply Cable, 7/8" Power Double-Ended Cordset: Male straight to Female straight, 3-pin(2+PE), black body, 63 V, 12 A; PUR black cable, 1.00 mm²


Product Description

0905 203 302 - DeviceNet Power Supply Cable, 7/8" Double-Ended Cordset: Male straight to Female straight, 3-pin(2+PE), black body, 63 V, 12 A; PUR black cable, 1.00 mm²

Technical Drawing




MALE FACE VIEW



1 = BK 1
2 = GN/YE
3 = BK 2

FEMALE FACE VIEW



1 = BK 1
2 = GN/YE
3 = BK 2

Technical Specifications

Product Description

Product Family:	Power Connector
Brand:	Lumberg Automation
Connector Type:	Cordset, double ended
Shielding:	Unshielded
Rated Voltage:	63 V
Operating Voltage:	≤ 50V AC / 60V DC
Rated Current*:	12 A

Technical Data Side 1

Product Sub Family:	7/8"
Type of Contact / Gender:	Male
Connector Design:	Straight
Attachment Type:	Coupling Nut [external threaded]
Number of Pins:	3
Coding:	A
Contact Resistance:	10 mOhm
Insulation Resistance:	10 ⁹ Ohm
Ambient Temperature (Operation)*:	-40 °C to +90 °C
Pollution Degree:	3 acc. to DIN EN 60664-1 (VDE 0110-1)
Contact Base Material:	CuZn

Contact Plating:	Ag/Au
Contact Bearer Material:	TPU
Contact Bearer Color:	Black
Molded Body Material:	TPU
Molded Body Color:	Black
Attachment Material:	PA

Cable Data

Cable Number:	203
Conductor Size:	1 mm²
Number of Wires:	3
Minimal Bending Radius (Fixed Inst):	> 5 x D
Minimal Bending Radius (Flexible Inst):	> 10 x D
Cable Jacket Material:	PUR
Cable Jacket Color:	Black
Cable Diameter D:	Ø 6.5 mm
Wire Insulation Material:	PVC
Insulated Wire Diameter:	Ø 2.2 mm
Ambient Temperature (Fixed Installation):	-40 °C to +90°C
Ambient Temperature (Flex Installation):	-5 °C to +90°C
Ambient Temperature (Drag Chain Inst):	-5 °C to +60°C
Flammability Class (Cable Jacket):	VDE 0482-265-2-1, EN 50265-2-1, IEC 60332-1
Cable Characteristics:	Continuous Flex cable; Resistances against, Oil, Grease ,Coolant, Tear, Vibration, UV, and Abrasion

Technical Data Side 2

Product Sub Family, Side 2:	7/8" Circular Connectors
Type of Contact / Gender, Side 2:	Female
Connector Design, Side 2:	Straight
Attachment Type, Side 2:	Coupling Nut [internal threaded]
Number of Pins, Side 2:	3
Coding, Side 2:	A
Contact Resistance, Side 2:	10 mOhm
Insulation Resistance, Side 2:	10^9 Ohm
Ambient Temperature (Operation), Side 2*:	-40 °C to +90 °C
Pollution Degree, Side 2:	3 acc. to DIN EN 60664-1 (VDE 0110-1)
Contact Base Material, Side 2:	CuZn
Contact Plating, Side 2:	Ag/Au
Contact Bearer Material, Side 2:	TPU
Contact Bearer Color, Side 2:	Black
Molded Body Material, Side 2:	TPU
Molded Body Color, Side 2:	Black
Attachment Material, Side 2:	PA
Attachment Plating, Side 2:	Black
Note, Side 2:	Do not connect or disconnect under load

Safety & Environmental Compliance

RoHS Compliant:	Yes
-----------------	-----

Resistances

Halogenfree:	Yes
Oil Resistance:	Yes

Notes

Note Derating:	Notice derating
----------------	-----------------

History

Update and Revision:	Revision Number: 0.32 Revision Date: 03-27-2024
----------------------	---

Variants

Item #	Item Description	Cable Length
71289	0905 203 302/0,6 M	0.6 m
12534	0905 203 302/3 M	3 m
12535	0905 203 302/5 M	5 m

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.