




Product: [0985 856 117](#) 

Industrial Ethernet double-ended cordset, high-flex, male RJ45 to male RJ45 straight, 4-pair, 24 AWG, TPE cable, stranded/shielded with teal jacket.

Product Description

Industrial Ethernet double-ended cordset, high-flex, male RJ45 to male RJ45 straight, 4-pair, 24 AWG, TPE cable, stranded/shielded with teal jacket.

Technical Specifications

Product Description

Brand:	Lumberg Automation
Connector Type:	Cordset, double ended
Data Transmission Rate:	100 Mbit/s

Technical Data Side 1

Connector Design:	Straight
Attachment Type:	Coupling Screw
Coding, Side 1:	A
Side 1 Contact Resistance:	≤ 10 mOhm
Ambient Temperature (Operation)*:	-40° C(-40°F) to +75° C(+167°F)
Side 1 Design Standard:	IEC 61076-2-101
Side 1 Pollution Degree:	3 acc. to DIN EN 60664-1 (VDE 0110-1)
Clearance / Creepage Distance:	EN 60664-1 (2008/01); VDE 0110-1
Contact Base Material:	Copper and Tin (CuSn)
Side 1 Contact Plating:	Copper over Gold (Cu/Au)
Contact Bearer Material:	PUR
Contact Bearer Color:	Black
Flammability Class (Contact Bearer):	UL 94 HB
Molded Body Material:	PUR, black
Flammability Class (Molded Body):	UL 94 HB
Attachment Material:	Brass (Cu/Zn)
Attachment Plating:	Nickel (Ni)

Cable Data

Cable Number:	856
Conductor Size:	24 AWG
Cycles (Bending):	> 5 M
Cable Jacket Material:	Thermoplastic Elastomer (TPE)
Cable Jacket Color:	Teal
Cable Diameter D:	7.6 mm nominal
Foil shield:	Aluminum/polyester/aluminum foil, 100% coverage
Cable Characteristics:	600 V AWM 20626, C(UL) US CMR, CSA FT4
Core Colors:	white/orange, orange, white/blue, blue, white/green, green, white/brown,brown

Technical Data Side 2

Attachment Type, Side 2:	RJ45
--------------------------	------

Contact Base Material, Side 2:	P / CuSN
Contact Plating, Side 2:	Au
Contact Bearer Material, Side 2:	Polycarbonate
Flammability Class (Contact Bearer), Side 2:	UL 94 HB
Molded Body Material, Side 2:	PUR, black
Flammability Class (Molded Body), Side 2:	UL 94 HB
Attachment Material, Side 2:	Plastic
Attachment Plating, Side 2:	Au

History

Update and Revision:	Revision Number: 0.10 Revision Date: 04-30-2026
----------------------	---

Variants

Item #	Item Description	Color
900016133	0985 856 117/0.5M	Color, Match Request
900016442	0985 856 117/0.3M	
900016443	0985 856 117/1M	

© 2026 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.