



**Part Number:** 1096A

600V Tray, (24 triad) 18 AWG (7x26) BC, PVC-NYL/PVC, IS/OS, TC-ER

[Request Sample](#)

**Product Description**

Twenty-four 18 AWG triads stranded (7x26) bare copper conductors, twisted triads, PVC/Nylon insulation, Individual and overall Beldfoil® shield (100% coverage), PVC jacket.

**Technical Specifications**

**Physical Characteristics (Overall)**

**Conductor**

AWG	Stranding	Material	No. of Triads
18	7x26	BC - Bare Copper	24

Conductor Count:	72
Total Number of Pairs:	N/A
Total Number of Triads:	24
Conductor Size:	18 AWG

**Insulation**

Material	Nominal Diameter
PVC/Nylon - Polyvinyl Chloride/Nylon	0.088 in

**Color Chart**

Number	Color
1	Black printed #1
2	Black printed #2
3	Black printed #3
4	Black printed #4
5	Black printed #5
6	Black printed #6
7	Black printed #7
8	Black printed #8
9	Black printed #9
10	Black printed #10
11	Black printed #11
12	Black printed #12
13	Black printed #13
14	Black printed #14
15	Black printed #15
16	Black printed #16
17	Black printed #17
18	Black printed #18
19	Black printed #19
20	Black printed #20
21	Black printed #21
22	Black printed #22
23	Black printed #23
24	Black printed #24

**Color Chart 2**

Number	Color
1	Black & White & Red and numbered 1
2	Black & White & Red and numbered 2
3	Black & White & Red and numbered 3
4	Black & White & Red and numbered 4
5	Black & White & Red and numbered 5
6	Black & White & Red and numbered 6
7	Black & White & Red and numbered 7
8	Black & White & Red and numbered 8
9	Black & White & Red and numbered 9
10	Black & White & Red and numbered 10
11	Black & White & Red and numbered 11
12	Black & White & Red and numbered 12
13	Black & White & Red and numbered 13
14	Black & White & Red and numbered 14
15	Black & White & Red and numbered 15
16	Black & White & Red and numbered 16
17	Black & White & Red and numbered 17
18	Black & White & Red and numbered 18
19	Black & White & Red and numbered 19
20	Black & White & Red and numbered 20
21	Black & White & Red and numbered 21
22	Black & White & Red and numbered 22
23	Black & White & Red and numbered 23
24	Black & White & Red and numbered 24

#### Inner Shield Material

Type	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Tape	Aluminum Foil-Polyester Tape	Beldfoil®	100 %	TC - Tinned Copper	20	7x28 mm

#### Outer Shield Material

Type	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Tape	Aluminum/Polyester	Beldfoil®	100 %	TC - Tinned Copper	18	7x26 mm

#### Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness	Ripcord
PVC - Polyvinyl Chloride	1.291 in	0.084 in	Yes

## Construction and Dimensions

#### Stranding

##### Twists

4.8 twist/ft

#### Cabling

##### Twists

0.77 twist/ft

## Electrical Characteristics

#### Conductor DCR

Nominal Conductor DCR	Nominal Inner Shield DCR	Nominal Outer Shield DCR
5.86 Ohm/1000ft	7.11 Ohm/1000ft	4 Ohm/1000ft

#### Current

##### Max. Recommended Current [A]

5 Amps per conductor @ 25°C

#### Voltage

##### UL Voltage Rating

600 V RMS

150 V RMS

## Temperature Range

UL Temp Rating:	75°C Dry, 90°C Wet
Wet Temp Range:	-30°C To +75 °C
Dry Temp Range:	-30°C To +90 °C

## Mechanical Characteristics

Bulk Cable Weight:	860 lbs/1000ft
Max Recommended Pulling Tension:	1971 lbs
Min Bend Radius/Minor Axis:	13 in

## Standards

NEC/(UL) Specification:	NPLF, TC
Other Specification:	ICEA S-73-532, S-61-402

## Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

## Suitability

Suitability - Burial:	Yes
Suitability - Sunlight Resistance:	Yes

## Flammability, LSOH, Toxicity Testing

C(UL) Flammability:	FT4
UL Flammability:	UL1685 UL Loading
IEEE Flammability:	1202
UL voltage rating:	600 V RMS

## Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.