



Product: [10GX63F](#)

10GX Category 6A Enhanced Cable, 4 Bonded-Pairs, F/UTP, CMP

Product Description

10GX Category 6A Enhanced Premise Horizontal Cable (625MHz), 4 Bonded-Pairs, 23 AWG Solid Bare Copper Conductors, F/UTP - Foil Shielded, Plenum-CMP, Flamarrest® PVC-LS Jacket

Technical Specifications

Product Overview

| | |
|------------------------|--|
| Suitable Applications: | Premise Horizontal Cable, Ethernet up to 10GBASE-T, Wi-Fi 6, Wi-Fi 5, Surveillance, HDBaseT, PoE++, PoE+, PoE, Noisy Environments |
| Patent: | This product has one or more applicable patents. More information on patents can be found at https://www.belden.com/patents . |

Construction Details

Conductor

| Size | Stranding | Material | No. of Pairs |
|--------|-----------|------------------|--------------|
| 23 AWG | Solid | BC - Bare Copper | 4 |

Insulation

| Material | Color Code |
|--------------------------------------|--|
| FEP - Fluorinated Ethylene Propylene | White & Blue, White & Orange, White & Green, White & Brown |

| | |
|--------------|-----|
| Bonded-Pair: | Yes |
|--------------|-----|

Inner Jacket

| Material | Nom. Diameter | Ripcord |
|--------------------------|------------------|---------|
| PVC - Polyvinyl Chloride | 0.26 in (6.6 mm) | Yes |

Outer Shield

| Shield Type | Material | Coverage | Drainwire Type |
|-------------|-------------------------|----------|------------------|
| Tape | Bi-Laminate (Alum+Poly) | 100% | 26 AWG (7x34) TC |

Outer Jacket

| Separator | Material | Material Trade Name | Nom. Diameter | Ripcord |
|------------------------------------|--------------------------|---------------------|--------------------|---------|
| Center Member (Patented X-Spline®) | PVC - Polyvinyl Chloride | Flamarrest® | 0.310 in (7.87 mm) | Yes |

| | |
|-----------------------------------|--------------------|
| Overall Cable Diameter (Nominal): | 0.310 in (7.87 mm) |
|-----------------------------------|--------------------|

Electrical Characteristics

Electricals

| Max. Conductor DCR | Max. Capacitance Unbalance |
|---------------------------|----------------------------|
| 82 Ohm/km (25 Ohm/1000ft) | 90 pF/100m |

Delay

| Frequency | Max. Delay | Max. Delay Skew | Nom. Velocity of Prop. |
|-----------|---------------|-----------------|------------------------|
| 100 MHz | 537.6 ns/100m | 45 ns/100m | 64% |

High Frequency

| Frequency [MHz] | Max. Insertion Loss (Attenuation) | Min. PSNEXT [dB] | Min. PSACR [dB] | Min. ACRF (ELFEXT) [dB] | Min. PSACRF (PSELFEXT) [dB] | Min. RL (Return Loss) [dB] | Max./Min. Input Impedance (unFitted) [Ohm] | Max./Min. Fitted Impedance [Ohm] | Min. PSANEXT [dB] | Min. PSAACRF [dB] | Min. TCL [dB] | Min. ELTCTL [dB] |
|-----------------|-----------------------------------|------------------|-----------------|-------------------------|-----------------------------|----------------------------|--|----------------------------------|-------------------|-------------------|---------------|------------------|
| 1 | 2.1 dB/100m | 73.3 | 71.2 | 70.8 | 68.8 | 20.0 | 100 ± 15 | 105 ± 10 | 77.0 | 77.0 | 40.0 | 35.0 |
| 4 | 3.8 dB/100m | 64.3 | 60.5 | 58.8 | 56.8 | 23.0 | 100 ± 15 | 100 ± 15 | 77.0 | 76.2 | 40.0 | 23.0 |
| 8 | 5.3 dB/100m | 59.8 | 54.4 | 52.7 | 50.7 | 24.5 | 100 ± 15 | 100 ± 15 | 77.0 | 70.1 | 40.0 | 16.9 |
| 10 | 5.9 dB/100m | 58.3 | 52.4 | 50.8 | 48.8 | 25.0 | 100 ± 15 | 100 ± 15 | 77.0 | 68.2 | 40.0 | 15.0 |
| 16 | 7.5 dB/100m | 55.2 | 47.8 | 46.7 | 44.7 | 25.0 | 100 ± 15 | 100 ± 15 | 77.0 | 64.1 | 38.0 | 10.9 |
| 20 | 8.4 dB/100m | 53.8 | 45.4 | 44.8 | 42.8 | 25.0 | 100 ± 15 | 100 ± 15 | 77.0 | 62.2 | 37.0 | 9.0 |
| 25 | 9.4 dB/100m | 52.3 | 43.0 | 42.8 | 40.8 | 25.0 | 100 ± 15 | 100 ± 15 | 77.0 | 60.2 | 36.0 | 7.0 |
| 31.25 | 10.5 dB/100m | 50.9 | 40.4 | 40.9 | 38.9 | 25.0 | 100 ± 15 | 100 ± 10 | 77.0 | 58.3 | 35.1 | |
| 62.5 | 15.0 dB/100m | 46.4 | 31.4 | 34.9 | 32.9 | 25.0 | 100 ± 15 | 100 ± 10 | 77.0 | 52.3 | 32.0 | |
| 100 | 19.1 dB/100m | 43.3 | 24.2 | 30.8 | 28.8 | 25.0 | 100 ± 15 | 100 ± 10 | 72.5 | 48.2 | 30.0 | |
| 200 | 27.6 dB/100m | 38.8 | 11.2 | 24.8 | 22.8 | 18.0 | 100 ± 22 | 100 ± 10 | 68.5 | 42.2 | 27.0 | |
| 250 | 31.1 dB/100m | 37.3 | 6.3 | 22.8 | 20.8 | 17.3 | 100 ± 32 | 100 ± 10 | 66.5 | 40.2 | 26.0 | |
| 300 | 34.3 dB/100m | 36.1 | 1.9 | 21.3 | 19.3 | 16.8 | 100 ± 32 | 100 ± 10 | 65.3 | 38.7 | 25.2 | |
| 350 | 37.2 dB/100m | 35.1 | -2.1 | 19.9 | 17.9 | 16.3 | 100 ± 32 | 100 ± 10 | 64.3 | 37.3 | 24.6 | |
| 400 | 40.1 dB/100m | 34.3 | | 18.8 | 16.8 | 15.9 | 100 ± 32 | 100 ± 10 | 63.5 | 36.2 | 24.0 | |
| 450 | 42.7 dB/100m | 33.5 | | 17.7 | 15.7 | 15.5 | 100 ± 32 | 100 ± 10 | 62.7 | 35.1 | 23.5 | |
| 500 | 45.3 dB/100m | 32.8 | | 16.8 | 14.8 | 15.2 | 100 ± 32 | 100 ± 10 | 62.0 | 34.2 | 23.0 | |
| 550 | 47.7 dB/100m | 32.2 | | 14.9 | 14.0 | 14.9 | 100 ± 32 | 100 ± 10 | 62.4 | 34.4 | | |
| 600 | 50.1 dB/100m | 31.6 | | | 13.2 | 14.7 | 100 ± 32 | 100 ± 10 | 61.8 | 33.6 | | |
| 625 | 51.2 dB/100m | 31.4 | | | 12.9 | 14.5 | 100 ± 32 | 100 ± 10 | 61.6 | 33.3 | | |
| 750 | 56.7 dB/100m | 30.2 | | | 11.3 | 14.0 | 100 ± 32 | 100 ± 10 | 60.4 | 31.7 | | |
| 860 | 61.2 dB/100m | 29.3 | | | 10.1 | 13.6 | 100 ± 32 | 100 ± 10 | 59.5 | 30.5 | | |

Voltage

| |
|--------------------------|
| UL Voltage Rating |
| 300 V (CMP) |

Mechanical Characteristics

Temperature

| UL Temperature | Operating | Installation | Storage |
|----------------|----------------|--------------|----------------|
| 75°C | -20°C To +75°C | 0°C To +50°C | -20°C To +75°C |

Bend Radius

| Stationary Min. | Installation Min. |
|-----------------|-------------------|
| 1.2 in (30 mm) | 3.0 in (76 mm) |

| | |
|--------------------|----------------|
| Max. Pull Tension: | 40 lbs (18 kg) |
| Bulk Cable Weight: | 48 lbs/1000ft |

Standards and Compliance

| | |
|----------------------------------|---|
| Environmental Suitability: | Plenum, Indoor |
| Sustainability: | Product Lens™, Environmental Product Declaration (EPD) Available |
| Flammability / Reaction to Fire: | NFPA 262, UL 910 (Plenum), FT6, IEC 60332-1-2 |
| CPR Compliance: | CPR Euroclass: Eca; CPR UKCA Class: Eca |
| NEC / UL Compliance: | Article 800, CMP |
| CEC / C(UL) Compliance: | CMP |
| ICEA Compliance: | S-116-732 |
| IEEE Compliance: | IEEE 802.3bt Type 1, Type 2, Type 3, Type 4 |
| NEMA Compliance: | ANSI/NEMA WC-66 |
| Data Category: | Category 6A |
| TIA/EIA Compliance: | ANSI/TIA-568.2-D Category 6A |
| ISO/IEC Compliance: | ISO/IEC 11801-1, IEC 61156-5 |
| European Directive Compliance: | EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), REACH, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE), REACH: 2020-01-16 |
| UK Regulation Compliance: | UKCA Mark |
| APAC Compliance: | China RoHS II (GB/T 26572-2011) |
| Non-Plenum Number: | 10GX62F |

Product Notes

| | |
|--------|--|
| Notes: | Electrical values are expected performance based on cable testing and representative performance within a typical Belden system. Values above 625 MHz are for Engineering Information Only. Print Includes Descending Footage/Meter Markings from Max. Put-Up Length to 0. |
|--------|--|

History

| | |
|----------------------|--|
| Update and Revision: | Revision Number: 0.553 Revision Date: 04-29-2024 |
|----------------------|--|

Part Numbers

Variants

| Item # | Color | Putup Type | Length | UPC | Footnote |
|-----------------|--------|------------|----------|--------------|----------|
| 10GX63F 0101000 | Black | Reel | 1,000 ft | 612825102526 | |
| 10GX63F D151000 | Blue | Reel | 1,000 ft | 612825102472 | |
| 10GX63F 0081000 | Gray | Reel | 1,000 ft | 612825102502 | C |
| 10GX63F 0021000 | Red | Reel | 1,000 ft | 612825102489 | |
| 10GX63F 0091000 | White | Reel | 1,000 ft | 612825102519 | |
| 10GX63F 0041000 | Yellow | Reel | 1,000 ft | 612825102496 | |

© 2025 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.