



**Product:** [10GXW53](#)

10GXW (0.265") Category 6A Cable, 4 Pair, F/UTP, CMP

## Product Description

10GXW Category 6A Enhanced Premise Horizontal Cable (500MHz), 4 Pair, 23 AWG Solid Bare Copper Conductors, F/UTP - Foil Shielded, Plenum-CMP, Flamarrest® PVC-LS Jacket

## Technical Specifications

### Product Overview

Suitable Applications:	Premise Horizontal Cable, Ethernet up to 10GBASE-T, Wi-Fi 6, Wi-Fi 5, Surveillance, HDBaseT, PoE++, PoE+, PoE, Noisy Environments
Patent:	This product has one or more applicable patents. More information on patents can be found at <a href="https://www.belden.com/patents">https://www.belden.com/patents</a> .

### Construction Details

#### Conductor

Size	Stranding	Material	No. of Pairs
23 AWG	Solid	BC - Bare Copper	4

#### Insulation

Material	Color Code
FEP - Fluorinated Ethylene Propylene	White & Blue, White & Orange, White & Green, White & Brown

#### Outer Shield

Shield Type	Material	Coverage
Tape	Bi-Laminate (Alum+Poly)	100%

#### Outer Jacket

Material	Nom. Diameter
PVC - Polyvinyl Chloride	0.265 in (6.73 mm)

### Electrical Characteristics

#### Electricals

Max. Conductor DCR	Max. Capacitance Unbalance
82 Ohm/km (25 Ohm/1000ft)	45 pF/100m

#### Delay

Max. Delay	Nom. Velocity of Prop.
537.6 ns/100m	69%

#### Voltage

UL Voltage Rating
300 V (CMP)

### Mechanical Characteristics

#### Temperature

UL Temperature	Operating	Installation	Storage
105°C	-20°C To +75°C	0°C To +50°C	-20°C To +75°C

## Bend Radius

### Installation Min.

2.65 in (67.3 mm)

Max. Pull Tension:	25 lbs (11 kg)
Bulk Cable Weight:	37 lbs/1000 ft

## Standards and Compliance

Environmental Suitability:	Plenum, Indoor
Flammability / Reaction to Fire:	NFPA 262 Plenum (UL 910), FT6
CEC / C(UL) Compliance:	CMP
ICEA Compliance:	S-116-732
IEEE Compliance:	IEEE 802.3bt Type 1, Type 2, Type 3, Type 4
NEMA Compliance:	ANSI/NEMA WC-66
Data Category:	Category 6A
TIA/EIA Compliance:	ANSI/TIA-568.2-D Category 6A
ISO/IEC Compliance:	ISO/IEC 11801-1, IEC 61156-5
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), REACH, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)

## Product Notes

Notes:	Electrical values are expected performance based on cable testing and representative performance within a typical system.
--------	---

## History

Update and Revision:	Revision Number: 0.41 Revision Date: 04-29-2024
----------------------	---

## Part Numbers

### Variants

Item #	Color	Putup Type	Length
10GXW53 0101000	Black	Reel	1,000 ft
10GXW53010Z1000	Black	ReelTuff Box	1,000 ft
10GXW53 D151000	Blue	Reel	1,000 ft
10GXW53D15Z1000	Blue	ReelTuff Box	1,000 ft
10GXW53 0081000	Gray	Reel	1,000 ft
10GXW53 0051000	Green, Dark	Reel	1,000 ft
10GXW53 0031000	Orange	Reel	1,000 ft
10GXW53 0021000	Red	Reel	1,000 ft
10GXW53 0071000	Violet	Reel	1,000 ft
10GXW53 0091000	White	Reel	1,000 ft
10GXW53009Z1000	White	ReelTuff Box	1,000 ft
10GXW53 0041000	Yellow	Reel	1,000 ft

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.