



Product: [127953A](#)

DataTuff® Cat 6, (4 pr) 23 AWG Solid BC, PP/PVC/PVC, EtherNet/IP, Foil Shld, CMR, CMX, 600 V AWM, Alum Armor

[Request Sample](#)

Product Description

Four Cat 6 23 AWG Bonded-Pairs solid bare copper conductors, polypropylene insulation, FRPE spline center member, inner PVC jacket, overall Beldfoil® Shield (100% coverage), industrial grade oil- and UV-resistant PVC outer jacket, aluminum interlocked armor.

Technical Specifications

Product Overview

Suitable Applications:	in cabinet with high volt devices, such as motor control center, mining, outdoor, harsh environment, IIoT, factory or process automation, IP cameras and devices, data communication, etc. exposure to rodent, crush, or cut through force,
------------------------	---

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material
23	Solid	BC - Bare Copper

Conductor Count:	8
Total Number of Pairs:	4

Insulation

Material
PO - Polyolefin

Inner Jacket Material

Material
PVC - Polyvinyl Chloride

Outer Shield Material

Type	Material	Drainwire Material	Drainwire AWG
Tape	Bi-Laminate (Alum+Poly)	TC - Tinned Copper	24

Outer Jacket Material

Material	Nominal Diameter
PVC - Polyvinyl Chloride	0.695

Construction and Dimensions

Armor

Type of Armor	Material
Interlocked	Aluminum

Standards

NEC/(UL) Compliance:	CMR-CMX
CEC/C(UL) Compliance:	CMG, HL
IEC Compliance:	ISO/IEC 11801 Cat 6
TIA/EIA Compliance:	TIA/EIA Category 6

Suitability

Suitability - Sunlight Resistance:	Yes
------------------------------------	-----

Flammability, LSOH, Toxicity Testing

C(UL) Flammability:	FT4
UL Flammability:	UL 1666 (Riser)

History

Update and Revision:	Revision Number: 0.94 Revision Date: 02-18-2021
----------------------	---

© 2021 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.