



Product: [1302E](#)

CatSnake® Category 6A Cable, 4 Pair, S/FTP, PVC

Product Description

CatSnake® Category 6A Cable, 4 Pair, 24 AWG Stranded Bare Copper Conductors, S/FTP Shielded, PVC Jacket

Technical Specifications

Product Overview

Suitable Applications:	Category 6A Patch, Horizontal and Backbone Cable, CobraNET, eSnake, Ethersound, Digital audio over Ethernet; Ethernet up to 10GBASE-T
Patent:	This product has one or more applicable patents. More information on patents can be found at https://www.belden.com/resources/patents .

Construction Details

Conductor

AWG	Stranding	Material	Number of Pairs
24	7x32	BC - Bare Copper	4

Insulation

Element	Material	Nom. Insulation Diameter	Color Code
Individual shielded pair	PO - Polyolefin (Foam)	1.4	White & Blue, White & Orange, White & Green, White & Brown

Bonded-Pair: No

Inner Shield Material

Element	Shield Type	Material	Coverage
Individual shielded pair	Tape	Bi-Laminate (Alum+Poly)	100%

Outer Shield Material

Type	Material	Coverage
Braid	Tinned Copper (TC)	80%

Outer Jacket Material

Material	Nom. Diameter
PVC - Polyvinyl Chloride	0.311 in

Electrical Characteristics

Electricals

Max. Conductor DCR	Max. DCR Unbalance	Max. DCR Unbalanced Between Pairs [%]	Max. Capacitance Unbalance	Max. Mutual Capacitance	Nom. Mutual Capacitance	Nom. Velocity of Prop.	Max. Current
95 Ohm/km	2%	4%	1,600 pF/m	56 pF/m	17 pF/ft	77%	1.5 A

Delay

Max. Delay	Max. Delay Skew	Nom. Velocity of Propagation (VP) [%]
534 ns/100m	25 ns/100m	77%

High Freq

Frequency [MHz]	Max. Insertion Loss (Attenuation)	Min. NEXT [dB]	Min. PSNEXT [dB]	Min. ACR [dB]	Min. PSACR [dB]	Min. ACRF (ELFEXT) [dB]	Min. PSACRF (PSELFEXT) [dB]	Min. RL (Return Loss) [dB]	Min. PSANEXT	Min. PSAACRF	Min. TCL [dB]	Min. ELTCTL [dB]
1 MHz	2.5 dB/100m	75.3 dB	72.3 dB	72.8 dB	69.8 dB	68 dB	65 dB	20 dB	67 dB	67 dB	40 dB	35 dB

4 MHz	4.6 dB/100m	66.3 dB	63.3 dB	61.7 dB	58.7 dB	56 dB	53 dB	23 dB	67 dB	66.2 dB	34 dB	23 dB
10 MHz	7.1 dB/100m	60.3 dB	57.3 dB	53.2 dB	50.2 dB	48 dB	45 dB	25 dB	67 dB	58.2 dB	30 dB	15 dB
16 MHz	9 dB/100m	57.2 dB	54.2 dB	48.3 dB	45.3 dB	43.9 dB	40.9 dB	25 dB	67 dB	54.1 dB	28 dB	10.9 dB
31.2 MHz	12.6 dB/100m	52.9 dB	49.9 dB	50.4 dB	47.3 dB	38.1 dB	35.1 dB	23.6 dB	67 dB	48.3 dB	25.1 dB	5.1 dB
62.5 MHz	18 dB/100m	48.4 dB	45.4 dB	30.4 dB	27.4 dB	32.1 dB	9.1 dB	21.5 dB	65.6 dB	42.3 dB	22 dB	
100 MHz	23 dB/100m	45.3 dB	42.3 dB	22.3 dB	19.3 dB	28 dB	25 dB	20.1 dB	62.5 dB	38.2 dB	20 dB	
125 MHz	25.8 dB/100m	43.8 dB	40.8 dB	18 dB	15 dB	26.1 dB	23.1 dB	19.4 dB	61 dB	36.3 dB	19 dB	
200 MHz	33.1 dB/100m	40.8 dB	37.8 dB	7.7 dB	4.7 dB	22 dB	19 dB	18 dB	58 dB	32.2 dB	17 dB	
250 MHz	37.3 dB/100m	39.3 dB	36.3 dB	2 dB	-1 dB	20 dB	17 dB	17.3 dB	56.5 dB	30.2 dB	16 dB	
300 MHz	41.1 dB/100m	38.1 dB	35.1 dB	-3 dB	-6 dB	18.5 dB	15.5 dB	17.3 dB	55.3 dB	28.7 dB		
500 MHz	54.3 dB/100m	34.8 dB	31.8 dB	-19.5 dB	-22.5 dB	14 dB	11 dB	17.3 dB	52 dB	24.2 dB		

Voltage

UL Voltage Rating	Non-UL Voltage Rating
300 V RMS	300 V

Mechanical Characteristics

Temperature

Operating	Installation	Storage
-30°C To +60°C	0°C To +50°C	-30°C To +60°C

Bend Radius

Installation Min.
64 mm

Max. Pull Tension:	16.9 lbs
Bulk Cable Weight:	46.9 lbs

Standards and Compliance

Environmental Suitability:	Indoor (Not Riser or Plenum), Indoor, Outdoor
ICEA Compliance:	S-116-732-2013
IEEE Compliance:	IEEE 802.3bt Type 1, Type 2, Type 3, Type 4
NEMA Compliance:	ANSI/NEMA WC-66
Data Category:	Category 6A
TIA/EIA Compliance:	ANSI/TIA-568.2-D Category 5e
Cenelec Compliance:	EN 50173-1:2018, Segregation class according EN50174-2=c
European Directive Compliance:	EU Directive 2015/863/EU, EU Directive 2011/65/EU (ROHS II), EU Directive 2012/19/EU (WEEE), REACH: 2020-01-16
APAC Compliance:	China RoHS II (GB/T 26572-2011)

Part Number

Variants

Item #	Color	Putup Type	Length	UPC/EAN
1302E.00152	Black	Reel	152 m	8719605000873
1302E.00305	Black	Reel	305 m	8719605000897
1302E.009999	Black	Reel	499 m	8719605000910
1302E 010500	Black	Reel	500 ft	612825381631
1302E.00500	Black	Reel	500 m	8719605000903
1302E 0101000	Black	Reel	1,000 ft	612825381778
1302E 0101640	Black	Reel	1,640 ft	612825381761
1302E.003000	Black	Reel	3,000 m	8719605000880

Product Notes

Notes:	Electrical values are expected performance based on cable testing and representative performance within a typical Belden system.
--------	--

History

Update and Revision:	Revision Number: 0.421 Revision Date: 09-30-2020
----------------------	--

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.