



Product: <u>1312A</u> ☑

Speaker Cable, 4 C #12 Str BC-OFHC, PVC Jkt, CM, DIR BUR, Flexible

Product Description

Speaker Cable, 4 Conductor 12 AWG (168 x 34) Oxygen-Free Bare Copper (High Conductivity), PE Insulation, PVC Jacket, CM, Direct Burial, Flexible

Technical Specifications

Product Overview

Speaker Cable; Direct Bu	rial; Indoor/Outdoor Home Theater; In-Wall Speal	aker; Outdoor Speaker
s		
Element Size Stranding	Material	
12 AWG 168x34	BC - Bare Copper (High Conductivity)	
	3	

Outer Jacket

	Material	Nom. Thickness	Nom. Diameter
PVC -	- Polyvinyl Chloride	0.043 in (1.1 mm)	0.423 in (10.7 mm)
Cable	e Diameter (Nominal): 0.423 in (1	0.7 mm)

Electrical Characteristics

Electricals

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Nom. Velocity of Prop.	Max. Current
Conductor(s)	1.6 Ohm/1000ft (5.2 Ohm/km)	22.3 pF/ft (73.2 pF/m)	66%	18 Amps per conductor @ 25°C

Voltage

UL Voltage Rating 300 V (CM, CL3)

Mechanical Characteristics

Temperature

UL Temperature	Operating
75°C	-20°C To +75°C

Bend Radius

Stationary Min.	Installation Mi
4.2 in (110 mm)	4.2 in (110 mm
,	
Max. Pull Tension	on:
Bulk Cable Weig	ght:

Standards and Compliance

Environmental Suitability:	Indoor (Not Riser or Plenum), Indoor, Outdoor
Flammability / Fire Resistance:	UL1666 Riser
NEC / UL Compliance:	Article 725, Article 800, CL3, CM
CEC / C(UL) Compliance:	CM
European Directive Compliance:	EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)
Plenum Number:	6002UE

Product Notes

Notes:	Jacket has ROOM 1 2 3 4 5 6 7 8 9 0 ZONE A B C D printed on it.

History

Update and Revision:	Revision Number: 0.327 Revision Date: 10-13-2021

Variants

Item #	Color	Putup Type	Length	UPC
1312A 010500	Black	Reel	500 ft	612825111672
1312A 0101000	Black	Reel	1,000 ft	612825111665
1312A 008500	Gray	Reel	500 ft	612825111658
1312A 0081000	Gray	Reel	1,000 ft	612825111641
1312A 1SL500	White 1SL	Reel	500 ft	612825111696
1312A 1SL1000	White 1SL	Reel	1,000 ft	612825111689

© 2021 Belden, Inc

All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.