



Product: <u>1313A</u> ☑

Speaker Cable, 2 C #10 Str BC-OFHC, PVC Jkt, CM, DIR BUR, Flexible

Product Description

Speaker Cable, 2 Conductor 10 AWG (259 x 34) Oxygen-Free Bare Copper (High Conductivity), PE Insulation, PVC Jacket, CM, Direct Burial, Flexible

Technical Specifications

Product Overview

| Product Overview | | | | | | | | | |
|---|-------------------------------------|-----------------------|----------------------------|--|--|--|--|--|--|
| Suitable Applications: Speaker Cable; Direct Burial; Indoor/Outdoor Home Theater; In-Wall Speaker; Outdoor Speaker | | | | | | | | | |
| Construction Details | | | | | | | | | |
| | | | | | | | | | |
| Conductor | | | | | | | | | |
| Element No. of Elements | Size Stranding | | | | | | | | |
| Conductor(s) 2 | 10 AWG 259x34 | BC - Bare Copper (Hig | gh Conductivity) | | | | | | |
| Insulation | | | | | | | | | |
| Element Material | Nom. Thickness | Nom. Insulation Diam | eter Color Code | | | | | | |
| Conductor(s) PE - Polyethylene | 0.019 in (0.48 mm) | 0.17 in (4.3 mm) | Black, Red | | | | | | |
| Outer Jacket | | | | | | | | | |
| Material Nom. 1 | hickness Nom. I | Diameter | | | | | | | |
| PVC - Polyvinyl Chloride 0.044 i | n (1.1 mm) 0.428 in | (10.9 mm) | | | | | | | |
| Overall Cable Diameter (Nominal |): 0.428 in (10.9 mm |) | | | | | | | |
| Electrical Characteristic | s | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| Electricals | | | | | | | | | |
| Electricals Element Nom. Conductor | DCR Nom. Capacit | ance Cond-to-Cond N | om. Velocity of Prop | Max. Current | | | | | |
| | DCR Nom. Capacit 23.2 pF/ft (76. | | om. Velocity of Prop 6% | Max. Current 40 Amps per conductor @ 30°C | | | | | |
| Element Nom. Conductor | | | | | | | | | |
| Element Nom. Conductor Conductor(s) 1 Ohm/1000ft | | | | | | | | | |
| Element Nom. Conductor Conductor(s) 1 Ohm/1000ft Voltage | | | | | | | | | |
| Element Nom. Conductor Conductor(s) 1 Ohm/1000ft Voltage UL Voltage Rating 300 V (CM, CL3) | 23.2 pF/ft (76. | | | | | | | | |
| Element Nom. Conductor Conductor(s) 1 Ohm/1000ft Voltage UL Voltage Rating | 23.2 pF/ft (76. | | | | | | | | |
| Element Nom. Conductor Conductor(s) 1 Ohm/1000ft Voltage UL Voltage Rating 300 V (CM, CL3) | 23.2 pF/ft (76. | | | | | | | | |
| Element Nom. Conductor Conductor(s) 1 Ohm/1000ft Voltage UL Voltage Rating 300 V (CM, CL3) Mechanical Characterist | 23.2 pF/ft (76. | | | | | | | | |
| Element Nom. Conductor Conductor(s) 1 Ohm/1000ft Voltage UL Voltage Rating 300 V (CM, CL3) Mechanical Characterist | 23.2 pF/ft (76. | | | | | | | | |
| Element Nom. Conductor Conductor(s) 1 Ohm/1000ft Voltage UL Voltage Rating 300 V (CM, CL3) Mechanical Characterist Temperature UL Temperature Operating | 23.2 pF/ft (76. | | | | | | | | |
| Element Nom. Conductor Conductor(s) 1 Ohm/1000ft Voltage UL Voltage Rating 300 V (CM, CL3) Mechanical Characterist Temperature UL Temperature Operating 75°C -20°C To +75° | 23.2 pF/ft (76. | | | | | | | | |
| Element Nom. Conductor Conductor(s) 1 Ohm/1000ft Voltage UL Voltage Rating 300 V (CM, CL3) Mechanical Characterist Temperature UL Temperature Operating 75°C -20°C To +75° Bend Radius | 23.2 pF/ft (76. ics C | | | | | | | | |
| Element Nom. Conductor Conductor(s) 1 Ohm/1000ft Voltage UL Voltage Rating 300 V (CM, CL3) Mechanical Characterist Temperature UL Temperature Operating 75°C -20°C To +75° Bend Radius Stationary Min. Installation Min | 23.2 pF/ft (76. ics C | | | | | | | | |
| Element Nom. Conductor Conductor(s) 1 Ohm/1000ft Voltage UL Voltage Rating 300 V (CM, CL3) Amount of the second | 23.2 pF/ft (76. | | | | | | | | |

| Environmental Suitability: | Indoor (Not Riser or Plenum), Indoor, Outdoor, Burial |
|----------------------------------|---|
| Flammability / Reaction to Fire: | UL 1685 UL loading , IEC 60332-1-2 |
| CPR Compliance: | CPR Euroclass: Eca |
| NEC / UL Compliance: | Article 725, Article 800, CL3, CM |
| CEC / C(UL) Compliance: | СМ |
| European Directive Compliance: | EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE) |
| UK Regulation Compliance: | UKCA Mark |
| APAC Compliance: | China RoHS II (GB/T 26572-2011) |
| Plenum Number: | 6T00UP |

History

Notes:

Update and Revision: Revision Num

Revision Number: 0.492 Revision Date: 02-15-2024

Jacket has ROOM 1 2 3 4 5 6 7 8 9 0 ZONE A B C D printed on it.

Part Numbers

Variants

| Item # | Color | Putup Type | Length | UPC | Footnote |
|---------------|-----------|------------|----------|--------------|----------|
| 1313A 010500 | Black | Reel | 500 ft | 612825111733 | С |
| 1313A 0101000 | Black | Reel | 1,000 ft | 612825111726 | С |
| 1313A 008500 | Gray | Reel | 500 ft | 612825111719 | С |
| 1313A 0081000 | Gray | Reel | 1,000 ft | 612825111702 | С |
| 1313A 1SL500 | White 1SL | Reel | 500 ft | 612825111757 | С |
| 1313A 1SL1000 | White 1SL | Reel | 1,000 ft | 612825111740 | С |

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.