



Product: [1330A](#)

Fieldbus, 12 Pr #18 Str TC, PO Ins, IS/OS, PVC Jkt, CMG

[Request Sample](#)

Product Description

Fieldbus, 12 Pair 18AWG (7x26) Tinned Copper, PO Insulation, Individual & Overall Beldfoil® Shield, Orange PVC Outer Jacket, CMG

Technical Specifications

Product Overview

| | |
|------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Suitable Applications: | harsh environment digital and serial two-way communication, oil and gas extraction and refining sites, petrochemical, Profibus process automation or Foundation FieldBus process automation, extreme temperature environments, exposure to humidity/moisture, dust, and oil, remote locations long distance applications, etc. |
|------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

Physical Characteristics (Overall)

| Conductor | | | | | |
|------------------|-----|-----------|--------------------|------------------|--------------|
| Element | AWG | Stranding | Material | Nominal Diameter | No. of Pairs |
| Pair(s) | 18 | 7x26 | TC - Tinned Copper | 0.048 in | 12 |
| Conductor Count: | | 24 | | | |

| Material |
|--------------------|
| PP - Polypropylene |

| Color Chart | |
|--------------------|---------------------------|
| Number | Color |
| 1 | Blue, Orange and Numbered |
| 2 | |
| 3 | |
| 4 | |
| 5 | |
| 6 | |
| 7 | |
| 8 | |
| 9 | |
| 10 | |
| 11 | |
| 12 | |

| Type | Material | Material Trade Name | Coverage [%] | Drainwire AWG | Drainwire Construction n x D |
|------|-------------------------|---------------------|--------------|---------------|------------------------------|
| Tape | Bi-Laminate (Alum+Poly) | Beldfoil® | 100% | 20 | 7x28 |
| | Tinned Copper (TC) | | | | |

| Type | Material | Material Trade Name | Coverage [%] | Drainwire Material | Drainwire AWG | Drainwire Construction n x D |
|------|-------------------------|---------------------|--------------|--------------------|---------------|------------------------------|
| Tape | Bi-Laminate (Alum+Poly) | Beldfoil® | 100% | TC - Tinned Copper | 18 | 7x26 |

| Material | Nominal Diameter | Ripcord |
|--------------------------|------------------|---------|
| PVC - Polyvinyl Chloride | 0.81 in | Yes |

Construction and Dimensions

Stranding

| Twists |
|------------|
| 6 twist/ft |

Electrical Characteristics

Conductor DCR

| Individual Pair Nominal Shield DCR | Nominal Conductor DCR | Nominal Outer Shield DCR |
|------------------------------------|-----------------------|--------------------------|
| 7.5 Ohm/1000ft | 5.86 Ohm/1000ft | 4.9 Ohm/1000ft |

Capacitance

| Max. Capacitance Unbalance | Nom. Capacitance Conductor to Shield | Nom.Mutual Capacitance |
|----------------------------|--------------------------------------|------------------------|
| 1.2 pF/ft | 45 pF/ft | 24 pF/ft |

Inductance

| Nominal Inductance |
|--------------------|
| 0.19 µH/ft |

Impedance

| Nominal Characteristic Impedance |
|----------------------------------|
| 100 Ohm |

High Frequency (Nominal/Typical)

| Nom. Insertion Loss |
|---------------------|
| 0.08 dB/100ft |

Delay

| Nominal Velocity of Propagation (VP) [%] |
|------------------------------------------|
| 66% |

High Frequency

| Frequency [MHz] | Max. Insertion Loss (Attenuation) | Max./Min. Input Impedance (unFitted) |
|-----------------|-----------------------------------|--------------------------------------|
| 0.031 MHz | 0.091 dB/100ft | 100 Ohm |

Current

| Element | Max. Recommended Current [A] |
|---------------|------------------------------|
| Per Conductor | 5.2 Amps per Conductor |

Voltage

| UL Voltage Rating |
|-------------------|
| 300 V RMS |

| | |
|------------------------------------|---------------------------------------------------------------------|
| Electrical Characteristics Notes: | Max Propagation Delay Change From 7.812 kHz to 39.06 kHz: 518 pS/ft |
| Other Electrical Characteristic 2: | 31.25 KBits/sec |

Temperature Range

| | |
|------------------------------|-----------------|
| UL Temp Rating: | 105°C |
| Operating Temperature Range: | -40°C to +105°C |

Mechanical Characteristics

| | |
|------------------------------|---------|
| Oil Resistance: | Yes |
| UV Resistance: | Yes |
| Max. Pull Tension: | 688 lbs |
| Min. Bend Radius/Minor Axis: | 8.1 in |

Standards

| | |
|-----------------------|---------------------------------------|
| NEC Articles: | Article 725, Article 727, Article 800 |
| NEC/(UL) Compliance: | CMG, CMX-Outdoor, ITC, PLTC-ER |
| CEC/C(UL) Compliance: | CMG |

Applicable Environmental and Other Programs

| | |
|----------------------------------------------|-------------------------------|
| EU Directive 2000/53/EC (ELV): | Yes |
| EU Directive 2011/65/EU (RoHS 2): | Yes |
| EU Directive 2012/19/EU (WEEE): | Yes |
| EU Directive 2015/863/EU (RoHS 2 amendment): | Yes |
| EU Directive Compliance: | EU Directive 2003/11/EC (BFR) |
| EU CE Mark: | Yes |
| MII Order #39 (China RoHS): | Yes |

Suitability

| | |
|------------------------------------|----------|
| Suitability - Burial: | Yes - UL |
| Suitability - Indoor: | Yes |
| Suitability - Oil Resistance: | Yes |
| Suitability - Outdoor: | Yes |
| Suitability - Sunlight Resistance: | Yes |

Flammability, LSOH, Toxicity Testing

| | |
|--------------------|--------------------|
| UL Flammability: | UL1685 FT4 Loading |
| IEC Flammability: | IEC 60332-3-24 |
| IEEE Flammability: | 1202 |
| UL voltage rating: | 300 V RMS |

Plenum/Non-Plenum

| | |
|---------------|----|
| Plenum (Y/N): | No |
|---------------|----|

Related Part Numbers

Variants

| Item # | Color | Put-Up Type | Length | UPC |
|---------------|--------|------------------------|----------|--------------|
| 1330A 0031000 | Orange | Reel | 1,000 ft | 612825112075 |
| Footnote: | | C - CRATE REEL PUT-UP. | | |

History

| | |
|----------------------|--------------------------------------------------|
| Update and Revision: | Revision Number: 0.465 Revision Date: 12-22-2023 |
|----------------------|--------------------------------------------------|

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.