



Product: [14G0.75CY](#)

MachFlex™ 350CY, 13+1G C 0.75mm² Str BC, PVC Ins, PVC Inner Jkt, TCBS, PVC Outer Jkt

Product Description

MachFlex™ 350CY Control VDE Certified, 13 Conductor + 1 Ground 0.75mm² Stranded Bare Copper, PVC Insulation, PVC Inner Jacket, Tinned Copper Braid Shield, PVC Outer Jacket

Technical Specifications

Product Overview

Suitable Applications:	Applicable for occasional flexing or fixed installation connecting precision control sensors, multi axis control machines, temperature controllers, control panels, machine cutting tools, auxiliary equipment, motor speed control, production machinery and many more in noisy industrial environment.
------------------------	--

Physical Characteristics (Overall)

Conductor				
Element	AWG	Stranding	Material	No. of Conductors
Conductor(s)	0.75 mm²	Class 5	BC - Bare Copper	13
Ground	0.75 mm²	Class 5	BC - Bare Copper	1
Conductor Count: 14				

Insulation
Material
PVC - Polyvinyl Chloride

Color Chart

Color
Black #1
Black #2
Black #3
Black #4
Black #5
...
Black #13
Green/Yellow

Outer Shield	
Type	Material
Braid	Tinned Copper (TC)

Outer Jacket	
Material	Nominal Diameter
PVC - Polyvinyl Chloride	13.6 mm

Electrical Characteristics

Conductor DCR
Max. Conductor DCR
26 Ohm/km

Voltage

Dielectric Withstand Voltage	Non-UL Description	Non-UL Voltage Rating
4000 V	IEC:	300/500 V

Temperature Range

Installation Temperature Range:	40°C to +80°C
Operating Temperature Range:	15°C to +70°C

Mechanical Characteristics

Oil Resistance:	Yes
UV Resistance:	Yes
Bulk Cable Weight:	283 kg/km
Min. Bend Radius During Installation:	6 x OD
Min. Bend Radius During Operation:	20 x OD

Standards

Other Specification:	IEC 60227-5, EN 50525-2-51, VDE 0281-13
Third Party Performance Verification:	VDE Certification No. 40041970, VDE Registration No. 8770

Applicable Environmental and Other Programs

EU Directive 2011/65/EU (RoHS 2):	Yes
MII Order #39 (China RoHS):	Yes

Suitability

Suitability - Indoor:	Yes
Suitability - Oil Resistance:	Yes
Suitability - Outdoor:	Yes
Suitability - Sunlight Resistance:	Yes

Flammability, LS0H, Toxicity Testing

IEC Flammability:	IEC 60332-1-2
Other Flammability:	DIN VDE 0482-332-1-2, DIN EN 60332-1-2

Related Part Numbers

Variants

Item #	Color	Length
14G0.75CY 01050M	Black, RAL 9005	50 m
14G0.75CY 010100M	Black, RAL 9005	100 m
14G0.75CY 010200M	Black, RAL 9005	200 m
14G0.75CY 36850M	Clear, Transparent	50 m
14G0.75CY 368100M	Clear, Transparent	100 m
14G0.75CY 368200M	Clear, Transparent	200 m
14G0.75CY G8U50M	Gray, RAL 7001	50 m
14G0.75CY G8U100M	Gray, RAL 7001	100 m
14G0.75CY G8U200M	Gray, RAL 7001	200 m

History

Update and Revision:	Revision Number: 0.19 Revision Date: 04-08-2022
----------------------	---

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.