



Product: [1502ELW](#)

Media Control, #18-2c TC, #22-1pr TC, LSZH Jacket, Cca

Product Description

Multimedia Control Cable, Cca-Rated, 2-22 AWG stranded tinned copper pairs (data) with Datalene® insulation, Beldfoil® shield, drain, 1-18 AWG stranded tinned copper pair with LSZH insulation, unshielded, LSZH jacket

Technical Specifications

Product Overview

Suitable Applications:	Multi-Media Control, RS-422, RS-232, 60754-1, 60754-2, 61034, Limited Smoke, IEC 60332-1-2, Cca
------------------------	---

Physical Characteristics (Overall)

Conductor

Element	AWG	Stranding	Material	No. of Conductors	No. of Pairs
22 AWG	22	7x30	TC - Tinned Copper		1
18 AWG	18	16x30	TC - Tinned Copper	2	

Conductor Count:	4
------------------	---

Insulation

Element	Material	Material Trade Name	Nominal Diameter
18 AWG	PE - Polyethylene (Foam)	Datalene®	2.0 mm
22 AWG	LSZH - Low Smoke Zero Halogen (Flame Retardant)		1.74 mm

Color Chart

Number	Color
1	Blue & White
2	Red & Black

Inner Shield

Type	Layer	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire Diameter	Drainwire AWG	Drainwire Construction n x D
Tape	22 AWG Pair	Bi-Laminate (Alum+Poly)	Beldfoil®	100%	TC - Tinned Copper	0.6 mm	24	
								7x32

Outer Shield

Material
No Shield

Outer Jacket

Material	Nominal Diameter	Nominal Wall Thickness	Ripcord
LSZH - Low Smoke Zero Halogen (Flame Retardant)	7.9 mm	1.15 mm	Yes

Electrical Characteristics

Conductor DCR

Element	Nominal Conductor DCR	Nominal Conductor DCR Conductor Resistance
22 AWG	53.5 Ohm/km	53.5 Ohm/km
18 AWG	22.6 Ohm/km	22.6 Ohm/km

Capacitance

Element	Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
22 AWG Pair(s)	46 pF/m	125 pF/m
22 AWG Pair(s)		

Inductance

Element	Nominal Inductance
22 AWG	0.76 µH/m
18 AWG	0.55 µH/m

Impedance

Nominal Balanced Characteristic Impedance Description	Nominal Characteristic Impedance	Nominal Characteristic Impedance Description
22 AWG Pair	100 Ohm	22 AWG Pair

Current

Max. Recommended Current [A]
3.8 Amps per Conductor at 25°C (22 AWG)

Voltage

Voltage Rating [V]
300 V

Temperature Range

Operating Temperature Range:	-30°C To +80°C
------------------------------	----------------

Mechanical Characteristics

Min. Bend Radius/Minor Axis:	65 mm
------------------------------	-------

Standards

CPR Euroclass:	Cca-s1,d1,a1
----------------	--------------

Applicable Environmental and Other Programs

Environmental Space:	Indoor - Euroclass Cca
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/11/EC (BFR):	Yes
EU Directive 2011/65/EU (RoHS 2):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU (RoHS 2 amendment):	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes

Suitability

Suitability - Indoor:	Yes
Suitability - Non-Halogenated:	Yes
Suitability - Outdoor:	Yes
Suitability - Sunlight Resistance:	Yes

Flammability, LS0H, Toxicity Testing

IEC Flammability:	IEC 60332-1-2
IEC 60754-1 - Halogen Amount:	Zero
IEC 60754-2 - Halogen Acid Gas Amount - Max. Conductivity:	2.5 µS/mm
IEC 60754-2 - Halogen Acid Gas Amount - Min. pH:	4.3

Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

History

Update and Revision:	Revision Number: 0.63 Revision Date: 03-15-2024
----------------------	---

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.