



Product: [1671J](#)



Conformable Coax, 50 Ohm RG-405, 24 AWG Solid SCCS, Copper-Tin Composite Shield, PVC Jacket

Product Description

Conformable Coax, 50 Ohm, RG-405, 24 AWG Solid Silvered Copper Covered Steel Conductor, PTFE Insulation, Copper Tape + 100% Tin-Filled Composite Braid Shield, PVC Jacket

Technical Specifications

Product Overview

| | |
|------------------------|--|
| Suitable Applications: | Microwave and other high frequency applications, Interconnect RF equipment, Radar equipment, Military communications |
|------------------------|--|

Construction Details

| | |
|----------|-----|
| RG Type: | 405 |
|----------|-----|

Conductor

| No. of Elements | Size | Stranding | Nom. Diameter | Material |
|-----------------|--------|-----------|---------------|--------------------------------------|
| 1 | 24 AWG | Solid | 0.0201 in | SCCS - Silvered Copper Covered Steel |

Insulation

| Material | Nom. Insulation Diameter | Color Code |
|--------------------------------|--------------------------|------------|
| PTFE - Polytetrafluoroethylene | 0.062 in (1.6 mm) | White |

Outer Shield

| Layer | Outer Shield Type | Material | Material Trade Name | Coverage |
|-------|-------------------|---------------------------------|---------------------|----------|
| 1 | Tape | Bare Copper (BC) | Beldfoil® | 100% |
| 2 | Braid | Tinned Copper (TC + Tin Filled) | | 100% |

Outer Jacket

| Material | Nom. Diameter |
|--------------------------|--------------------|
| PVC - Polyvinyl Chloride | 0.127 in (3.23 mm) |

| | |
|-----------------------------------|--------------------|
| Overall Cable Diameter (Nominal): | 0.127 in (3.23 mm) |
|-----------------------------------|--------------------|

Electrical Characteristics

VSWR

| Frequency | Max. VSWR |
|-----------|-----------|
| 500 MHz | 1.1:1 |
| 20000 MHz | 1.3:1 |

Attenuation

| Frequency | Nom. Attenuation |
|-----------|------------------|
| 500 MHz | 15 dB/100ft |
| 1000 MHz | 22.2 dB/100ft |
| 2000 MHz | 32.8 dB/100ft |
| 3000 MHz | 41.2 dB/100ft |
| 5000 MHz | 54.9 dB/100ft |
| 7000 MHz | 66.4 dB/100ft |
| 10000 MHz | 81.2 dB/100ft |

| | |
|-----------|--------------|
| 15000 MHz | 102.dB/100ft |
| 18000 MHz | 113 dB/100ft |
| 20000 MHz | 120 dB/100ft |

Power Rating

| Frequency | Max. Power Rating |
|------------|-------------------|
| 500 MHz | 180 W |
| 1,000 MHz | 119 W |
| 2,000 MHz | 79 W |
| 3,000 MHz | 62 W |
| 5,000 MHz | 46 W |
| 7,000 MHz | 37 W |
| 10,000 MHz | 30 W |
| 15,000 MHz | 24 W |
| 18,000 MHz | 21 W |
| 20,000 MHz | 20 W |

Electricals

| Nom. Conductor DCR | Nom. Outer Shield DCR | Nom. Capacitance Cond-to-Shield | Nom. Characteristic Impedance | Nom. Velocity of Prop. |
|------------------------------|-------------------------------|---------------------------------|-------------------------------|------------------------|
| 64.2 Ohm/1000ft (211 Ohm/km) | 10.2 Ohm/1000ft (33.5 Ohm/km) | 29.5 pF/ft (96.8 pF/m) | 50 Ohm | 70% |

Voltage

| UL Voltage Rating | Voltage Rating |
|-------------------|----------------|
| 30 V RMS | 1500 V RMS |

Mechanical Characteristics

Temperature

| UL Temperature | Operating |
|----------------|-----------------|
| 105°C | -40°C To +105°C |

Bend Radius

| Stationary Min. | Installation Min. | Flexing Min. |
|-----------------|-------------------|-------------------|
| 1 in (25 mm) | .125 in (3.18 mm) | .375 in (9.53 mm) |

| | |
|--------------------|----------------|
| Max. Pull Tension: | 26 lbs (12 kg) |
| Bulk Cable Weight: | 16 lbs/1000 ft |

Standards and Compliance

| | |
|----------------------------------|---|
| Environmental Suitability: | Indoor/Outdoor, Indoor, Outdoor |
| Flammability / Reaction to Fire: | Horizontal Wire |
| AWM Compliance: | AWM 10245 (30 V 105°C) |
| European Directive Compliance: | EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE) |
| APAC Compliance: | China RoHS II (GB/T 26572-2011) |

Product Notes

| | |
|--------|---|
| Notes: | Teflon® is a registered trademark of E. I. duPont de Nemours and Co. used under license by Belden, Inc. |
|--------|---|

History

| | |
|----------------------|--|
| Update and Revision: | Revision Number: 0.390 Revision Date: 05-03-2023 |
|----------------------|--|

Part Numbers

Variants

| Item # | Color | Putup Type | Length | UPC | Footnote |
|---------------|-------|------------|----------|--------------|----------|
| 1671J 010100 | Black | Reel | 100 ft | 612825120315 | |
| 1671J 010500 | Black | Reel | 500 ft | 612825120339 | V |
| 1671J 0101000 | Black | Reel | 1,000 ft | 612825120322 | V |

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.