



Product: [1671J](#)



Conformable Coax, 50 Ohm RG-405, 24 AWG Solid SCCS, Copper-Tin Composite Shield, PVC Jacket

Product Description

Conformable Coax, 50 Ohm, RG-405, 24 AWG Solid Silvered Copper Covered Steel Conductor, PTFE Insulation, Copper Tape + 100% Tin-Filled Composite Braid Shield, PVC Jacket

Technical Specifications

Product Overview

Suitable Applications:	Microwave and other high frequency applications, Interconnect RF equipment, Radar equipment, Military communications
------------------------	--

Construction Details

RG Type:	405
----------	-----

Conductor

No. of Elements	Size	Stranding	Nom. Diameter	Material
1	24 AWG	Solid	0.0201 in	SCCS - Silvered Copper Covered Steel

Insulation

Material	Nom. Insulation Diameter	Color Code
PTFE - Polytetrafluoroethylene	0.062 in (1.6 mm)	White

Outer Shield

Layer	Outer Shield Type	Material	Material Trade Name	Coverage
1	Tape	Bare Copper (BC)	Beldfoil®	100%
2	Braid	Tinned Copper (TC + Tin Filled)		100%

Outer Jacket

Material	Nom. Diameter
PVC - Polyvinyl Chloride	0.127 in (3.23 mm)

Overall Cable Diameter (Nominal):	0.127 in (3.23 mm)
-----------------------------------	--------------------

Electrical Characteristics

VSWR

Frequency	Max. VSWR
500 MHz	1.1:1
20000 MHz	1.3:1

Attenuation

Frequency	Nom. Attenuation
500 MHz	15 dB/100ft
1000 MHz	22.2 dB/100ft
2000 MHz	32.8 dB/100ft
3000 MHz	41.2 dB/100ft
5000 MHz	54.9 dB/100ft
7000 MHz	66.4 dB/100ft
10000 MHz	81.2 dB/100ft

15000 MHz	102.dB/100ft
18000 MHz	113 dB/100ft
20000 MHz	120 dB/100ft

Power Rating

Frequency	Max. Power Rating
500 MHz	180 W
1,000 MHz	119 W
2,000 MHz	79 W
3,000 MHz	62 W
5,000 MHz	46 W
7,000 MHz	37 W
10,000 MHz	30 W
15,000 MHz	24 W
18,000 MHz	21 W
20,000 MHz	20 W

Electricals

Nom. Conductor DCR	Nom. Outer Shield DCR	Nom. Capacitance Cond-to-Shield	Nom. Characteristic Impedance	Nom. Velocity of Prop.
64.2 Ohm/1000ft (211 Ohm/km)	10.2 Ohm/1000ft (33.5 Ohm/km)	29.5 pF/ft (96.8 pF/m)	50 Ohm	70%

Voltage

UL Voltage Rating	Voltage Rating
30 V RMS	1500 V RMS

Mechanical Characteristics

Temperature

UL Temperature	Operating
105°C	-40°C To +105°C

Bend Radius

Stationary Min.	Installation Min.	Flexing Min.
1 in (25 mm)	.125 in (3.18 mm)	.375 in (9.53 mm)

Max. Pull Tension:	26 lbs (12 kg)
Bulk Cable Weight:	16 lbs/1000 ft

Standards and Compliance

Environmental Suitability:	Indoor/Outdoor, Indoor, Outdoor
Flammability / Reaction to Fire:	Horizontal Wire
AWM Compliance:	AWM 10245 (30 V 105°C)
European Directive Compliance:	EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)

Product Notes

Notes:	Teflon® is a registered trademark of E. I. duPont de Nemours and Co. used under license by Belden, Inc.
--------	---

History

Update and Revision:	Revision Number: 0.390 Revision Date: 05-03-2023
----------------------	--

Part Numbers

Variants

Item #	Color	Putup Type	Length	UPC	Footnote
1671J 010100	Black	Reel	100 ft	612825120315	
1671J 010500	Black	Reel	500 ft	612825120339	V
1671J 0101000	Black	Reel	1,000 ft	612825120322	V

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.