


Product: [1794DNH](#) 

## COAX RG7/U LSZH-C HDTV PRECISION VIDEO



### Product Description

COAX [1.3/5.7] RG7/U LSZH-C HDTV CLASSICS PRO

### Technical Specifications

#### Product Overview

Suitable Applications:	Low loss HDTV/SDI Digital coax used in analog and digital video circuits and high quality applications; The outer conductor is designed for high screening attenuation and low transfer impedance; The cable is suitable for indoor and outdoor use
------------------------	---

#### Physical Characteristics (Overall)

##### Conductor

AWG	Stranding	Material	Nominal Diameter	Diameter +/- Tolerance	No. of Coax
16	Solid	BC - Bare Copper	1.295 mm	0.03 mm	1

Conductor Count:	1
------------------	---

##### Insulation

Type	Material	Nominal Diameter	Diameter +/- Tolerance
Dielectric	PE - Polyethylene (Foam)	5.715 mm	0.15 mm

##### Outer Shield Material

Type	Layer	Material	Coverage [%]	Min. Overlap	Nominal Diameter	Coverage +/- Tolerance
Tape	1	Tri-Laminate (Alum+Poly+Alum)	100%	2 mm		
Braid	2	Tinned Copper (TC)	80%		6.6 mm	5%
Tape	3	Bi-Laminate (Alum+Poly)	100%	2 mm		

##### Outer Jacket Material

Material	Nominal Diameter	Diameter +/- Tolerance
LSZH - Low Smoke Zero Halogen (Flame Retardant)	8.13 mm	0.2 mm

Table Notes:	According to EN 50290-2-20
--------------	----------------------------

#### Construction and Dimensions

Min Elongation at Breakof Jacket:	125 %
Min Tensile Strength of Jacket:	9 MPa

#### Electrical Characteristics

##### Conductor DCR

Nominal Conductor DCR	Nominal Outer Shield DCR
13.2 Ohm/km	9.2 Ohm/km

##### Capacitance

Nom. Capacitance	Capacitance Tolerance
53 pF/m	2 pF/m

##### Impedance

Nominal Characteristic Impedance	Nominal Characteristic Tolerance
----------------------------------	----------------------------------

75 Ohm	3 Ohm
--------	-------

#### High Frequency (Nominal/Typical)

Frequency [MHz]	Nom. Insertion Loss
1 MHz	0.56 dB/100m
3.6 MHz	1 dB/100m
10 MHz	1.6 dB/100m
71.5 MHz	4.1 dB/100m
135 MHz	5.6 dB/100m
270 MHz	8 dB/100m
360 MHz	9.3 dB/100m
540 MHz	11.5 dB/100m
720 MHz	13.4 dB/100m
750 MHz	13.7 dB/100m
1000 MHz	16.1 dB/100m
1500 MHz	20.1 dB/100m
2000 MHz	23.6 dB/100m
2250 MHz	25.2 dB/100m
3000 MHz	29.8 dB/100m
4500 MHz	37.8 dB/100m

#### Delay

Nominal Delay	Nominal Velocity of Propagation (VP) [%]	Velocity of Propagation Tolerance
400 ns/ft	84%	2%

#### High Freq

Frequency [MHz]	Min. RL (Return Loss) [dB]
5 - 1600 MHz	23 dB
1600 - 4500 MHz	21 dB

Table Notes: In each frequency band, 1 peak value up to 4 dB lower is allowed

#### Screening

Frequency [MHz]	Min. Screening Attenuation After Flexing
30 - 1000 MHz	95 dB
1000 - 2000 MHz	85 dB
2000 - 3000 MHz	75 dB
3000 - 4500 MHz	65 dB

Screening Class: A+

#### Transfer Impedance

Transfer Impedance
Max. 2.5 mOhm/m

#### Voltage

Voltage Test Dielectric
2.0 kV DC

#### Temperature Range

Installation Temp Range:	-5°C To +50°C
Storage Temp Range:	-30°C To +70°C
Operating Temp Range:	-30°C To +70°C

#### Mechanical Characteristics

Max. Pull Tension:	500 N
Min Bend Radius (W/o Pulling Strength):	80 mm

#### Standards

CPR Euroclass:	Dca-s2,d2,a1
CENELEC Compliance:	EN 50117-1
Series Type:	7

#### Applicable Environmental and Other Programs

Environmental Space:	Indoor - Euroclass Dca
EU RoHS Compliance Date (yyyy-mm-dd):	2011-12-27

## Flammability, LSOH, Toxicity Testing

IEC Flammability:	IEC 60332-1-2 and IEC 60332-3-24
Other Flammability:	CEI 20-22-3
IEC 60754-1 (EN50267-1)- Halogen Amount:	Zero
IEC 60754-2 (EN50267-2)- Halogen Acid Gas Amount - Max. Conductivity:	2.5 µS/mm
IEC 60754-2 (EN50267-2)- Halogen Acid Gas Amount - Min. pH:	4.3
IEC 61034-2 (EN 61034-2) (VDE 0482-1034) - Smoke Density Min. Transmittance:	60%

## Part Number

### Variants

Item #	Color	Putup Type	Length	EAN
1794DNH.04500	Green	Reel	500 m	8719605004079
1794DNH.01500	Purple	Reel	500 m	8719605004062

## History

Update and Revision:	Revision Number: 0.188 Revision Date: 02-12-2021
----------------------	--

© 2021 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.