

# Product: <u>1800F</u> ☑

Digital Microphone Cable, 1 Pr #24 Str BC, 95% TC French Braid, PVC Jkt, CL2R, Flexible

# **Product Description**

Digital Microphone Cable, 1 Pair 24 AWG (42x40) Bare Copper, PE insulation, 95% Tinned Copper French Braid Shield, Matte PVC jacket, CL2R-rated, Flexible

# **Technical Specifications**

Product Overview						
Suitable Applications: Digital microphone; Flexible i				le interconnect cable for digital audio		
Construction Details						
Conductor						
Element No	. of Elements	Size	Strandi	ng Material		
Pair(s) 1		24 AWG	6 42x40	BC - Bare Copper		
Insulation Element	Material		Nom. Th	nickness Nom. Insu	lation Diameter Color Code Notes	s
Pair(s) PE	- Polyethylene	(Foam)	0.017 in (	0.43 mm) 0.058 in (1	.5 mm) Red & Black HDPE	Ξ
Outer Shield						
Shield Type	Material	C	Coverage	Drainwire Type	Notes	
French Braid	Tinned Coppe	r (TC) 9	15%	26 AWG (30x40) BC	Paper tape under braid with drain over	er tape
Outer Jacket						
Material Nom. Thickness Nom. Diameter						
PVC - Polyvinyl Chloride 0.037 in (0.94 mm) 0.211 in (5.36 mm)						

#### Overall Cable Diameter (Nominal): 0.211 in (5.36 mm)

## **Electrical Characteristics**

### Electricals

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Nom. Capacitance Cond-to-Other (Conds + Shield)	Nom. Characteristic Impedence	Nom. Velocity of Prop.	Max. Current
Pair(s)	23.7 Ohm/1000ft	12 pF/ft (39 pF/m)	26 pF/ft (85 pF/m)	110 Ohm	76%	3.8 Amps per conductor @ 30°C

#### Voltage

Voltage Rating 100 V

# **Mechanical Characteristics**

#### Temperature

UL Temperature	Operating
60°C	-20°C to +60°C

Bend Radius

Stationary Min. Installation Min.

2.1 in (53 mm) 2.1 in (53 mm)					
Max. Pull Tension:	40 lbs (18 kg)				
Bulk Cable Weight:	23 lbs/1000ft				
Standards and Compliance					
Environmental Suitability:	Indoor - Riser, Indoor				
Flammability / Reaction to Fire:	UL 1666 Riser				
NEC / UL Compliance:	Article 725, CL2R				
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)				
APAC Compliance:	China RoHS II (GB/T 26572-2011)				
Other Standard Compliance(s):	AES/EBU				
History					

History

Update and Revision:

Revision Number: 0.521 Revision Date: 02-15-2024

#### **Part Numbers**

#### Variants

ltem #	Color	Putup Type	Length	UPC	Footnote
1800F B59500	Black, Matte	Reel	500 ft	612825122845	С
1800F B591000	Black, Matte	Reel	1,000 ft	612825122838	С
1800F B59U1000	Black, Matte	UnReel	1,000 ft	612825122821	
1800F B5910000	Black, Matte	Reel	10,000 ft	612825429944	
1800F G7XU1000	Blue, Matte	UnReel	1,000 ft	612825122876	
1800F U90U1000	Gray, Matte	UnReel	1,000 ft	612825122890	
1800F G7WU1000	Green, Matte	UnReel	1,000 ft	612825122869	
1800F G7VU1000	Red, Matte	UnReel	1,000 ft	612825122852	
1800F Z4BU1000	Violet Z4B	UnReel	1,000 ft	612825122906	
1800F G8MU1000	Yellow, Matte	UnReel	1,000 ft	612825122883	

### © 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.