



**Product:** [1802B](#)

Audio Cable, 2 Pair 24 AWG, TC, CMR

## Product Description

Digital Audio Cable, 2 pair 24 AWG stranded tinned copper with Datalene® insulation, Beldfoil® shield, drain, CMR PVC jacket, parallel construction.

## Technical Specifications

### Physical Characteristics (Overall)

#### Conductor

| AWG | Stranding | Material           | Nominal Diameter | No. of Pairs |
|-----|-----------|--------------------|------------------|--------------|
| 24  | 7x32      | TC - Tinned Copper | 0.024 in         | 2            |

|                        |   |
|------------------------|---|
| Conductor Count:       | 4 |
| Total Number of Pairs: | 2 |

#### Insulation

| Material                 | Material Trade Name | Nominal Diameter |
|--------------------------|---------------------|------------------|
| PE - Polyethylene (Foam) | Datalene®           | 0.68 in          |

#### Color Chart

| Number | Color       |
|--------|-------------|
| 1      | Red & Black |
| 2      | Red & Black |

#### Inner Shield Material

| Type | Material                | Material Trade Name | Coverage [%] | Drainwire Diameter | Drainwire AWG | Drainwire Construction n x D |
|------|-------------------------|---------------------|--------------|--------------------|---------------|------------------------------|
| Tape | Bi-Laminate (Alum+Poly) | Beldfoil®           | 100%         | 0.024 in           | 24            | 7x32                         |

|              |  |
|--------------|--|
| Table Notes: | Indiv. Foil tapes bonded to inner jacket |
|--------------|--|

#### Outer Shield Material

| Material  |
|-----------|
| No Shield |

#### Outer Jacket Material

| Material                 | Nominal Diameter |
|--------------------------|------------------|
| PVC - Polyvinyl Chloride | .180 x .360 in   |

### Electrical Characteristics

#### Conductor DCR

| Nominal Conductor DCR |
|-----------------------|
| 23.7 Ohm/1000ft       |

#### Capacitance

| Nom. Capacitance Conductor to Conductor | Nom. Capacitance Conductor to Other Conductor to Shield |
|---|---|
| 12 pF/ft                                | 26 pF/ft  |

#### Inductance

| Nominal Inductance |
|--------------------|
|--------------------|

0.18  $\mu$ H/ft

#### Impedance

##### Nominal Characteristic Impedance

110 Ohm

#### High Frequency (Nominal/Typical)

##### Nom. Insertion Loss

0.69 dB/100ft

0.93 dB/100ft

0.96 dB/100ft

1.07 dB/100ft

1.19 dB/100ft

1.21 dB/100ft

1.31 dB/100ft

1.41 dB/100ft

1.45 dB/100ft

1.57 dB/100ft

1.76 dB/100ft

1.83 dB/100ft

2.01 dB/100ft

2.24 dB/100ft

2.3 dB/100ft

3.08 dB/100ft

#### High Freq

##### Frequency [MHz]

0.384 MHz

0.7056 MHz

0.768 MHz

1.024 MHz

1.4112 MHz

1.536 MHz

2.048 MHz

2.8224 MHz

3.072 MHz

4.096 MHz

5.6448 MHz

6.144 MHz

8.192 MHz

11.2896 MHz

12.288 MHz

24.576 MHz

#### Current

##### Max. Recommended Current [A]

2.75 Amps per Conductor at 25°C

#### Voltage

##### UL Voltage Rating

300 V RMS

#### Temperature Range

UL Temp Rating: 60°C

Operating Temp Range: -30°C To +60°C

#### Mechanical Characteristics

UV Resistance: No

Bulk Cable Weight: 33 lbs/1000ft

Max. Pull Tension: 33 lbs

Min Bend Radius/Minor Axis: 2 in

## Standards

|                       |         |
|-----------------------|---------|
| NEC/(UL) Compliance:  | CMR     |
| CEC/C(UL) Compliance: | CMR     |
| Other Compliance:     | AES/EBU |

## Applicable Environmental and Other Programs

|                                       |                               |
|---------------------------------------|-------------------------------|
| Environmental Space:                  | Indoor (Not Riser or Plenum)  |
| EU Directive 2000/53/EC (ELV):        | Yes                           |
| EU Directive 2003/96/EC (BFR):        | Yes                           |
| EU Directive 2011/65/EU (ROHS II):    | Yes                           |
| EU Directive 2012/19/EU (WEEE):       | Yes                           |
| EU Directive 2015/863/EU:             | Yes                           |
| EU Directive Compliance:              | EU Directive 2003/11/EC (BFR) |
| EU CE Mark:                           | Yes                           |
| EU RoHS Compliance Date (yyyy-mm-dd): | 2004-01-01                    |
| MII Order #39 (China RoHS):           | Yes                           |

## Suitability

|                                    |     |
|------------------------------------|-----|
| Suitability - Aerial:              | No  |
| Suitability - Burial:              | No  |
| Suitability - Hazardous Locations: | No  |
| Suitability - Indoor:              | Yes |
| Suitability - Outdoor:             | No  |
| Suitability - Sunlight Resistance: | No  |

## Flammability, LSOH, Toxicity Testing

|                    |           |
|--------------------|-----------|
| CSA Flammability:  | FT4       |
| UL voltage rating: | 300 V RMS |

## Plenum/Non-Plenum

|               |    |
|---------------|----|
| Plenum (Y/N): | No |
|---------------|----|

## Part Number

### Variants

| Item #         | Color      | Putup Type          | Length   | UPC          |
|----------------|------------|---------------------|----------|--------------|
| 1802B 010N1000 | Black      | Reel w/Small Barrel | 1,000 ft | 612825123071 |
| 1802B Z4B5000  | Violet     | Reel                | 5,000 ft | 612825430018 |
| 1802B Z4B500   | Violet Z4B | Reel                | 500 ft   | 612825123064 |
| 1802B Z4B1000  | Violet Z4B | Reel                | 1,000 ft | 612825123057 |
| 1802B Z4BU1000 | Violet Z4B | UnReel              | 1,000 ft | 612825123040 |
| 1802B Z4BN1000 | Vio Z4B    | Reel w/Small Barrel | 1,000 ft | 612825123033 |

|           |                        |
|-----------|------------------------|
| Footnote: | C - CRATE REEL PUT-UP. |
|-----------|------------------------|

## Product Notes

|        |   |
|--------|---|
| Notes: | For cross-connect use with 1803F (et al.) Digital Audio Snake Cables. The jacket and shield are bonded so both can be removed on automatic stripping equipment. |
|--------|---|

## History

|                      |  |
|----------------------|--|
| Update and Revision: | Revision Number: 0.309 Revision Date: 02-16-2021 |
|----------------------|--|

© 2021 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.