



Product: [19350](#)

Portable Cordage, 3 C #18 Str BC, PVC Ins, PVC Jkt, UL Type SVT

[Request Sample](#)

Product Description

Portable Cordage, 3 Conductor 18AWG (42x34) Bare Copper, PVC Insulation, PVC Outer Jacket, UL Type SVT

Technical Specifications

Construction Details

Conductor

| Element | No. of Elements | Size | Stranding | Material |
|--------------|-----------------|--------|-----------|------------------|
| Conductor(s) | 3 | 18 AWG | 42x34 | BC - Bare Copper |

Insulation

| Material | Nom. Thickness | Nom. Insulation Diameter | Color Code |
|--------------------------|--------------------|--------------------------|---------------------|
| PVC - Polyvinyl Chloride | 0.018 in (0.46 mm) | 0.084 in (2.1 mm) | Green, Black, White |

Outer Jacket

| Separator | Material | Nom. Thickness | Nom. Diameter |
|------------|--------------------------|--------------------|---------------|
| Paper Tape | PVC - Polyvinyl Chloride | 0.325 in (8.26 mm) | 0.253 in |

Electrical Characteristics

Electricals

| Nom. Conductor DCR | Max. Current |
|--------------------|---|
| 6.97 Ohm/1000ft | 10 Amps per Conductor at 25°C (7 Amps over 50 ft) |
| | 7 Amps per Conductor at 25°C (over 50 ft) |

Voltage

| UL Voltage Rating |
|-------------------|
| 300 V |

Mechanical Characteristics

Temperature

| UL Temperature |
|----------------|
| 60°C |

| | |
|--------------------|--------------------|
| Max. Pull Tension: | 63.9 lbs (29.0 kg) |
| Bulk Cable Weight: | 39 lbs/1000ft |

Standards and Compliance

| | |
|--------------------------------|--|
| Environmental Suitability: | Oil Resistance |
| NEC / UL Compliance: | Article 400, SVT |
| AWM Compliance: | SVT |
| European Directive Compliance: | EU CE Mark, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE) |
| APAC Compliance: | China RoHS II (GB/T 26572-2011) |

History

Part Numbers

Variants

| Item # | Color | Putup Type | Length | UPC | Footnote |
|--------------|-------|------------|--------|--------------|----------|
| 19350 008250 | Gray | Reel | 250 ft | 612825126942 | F |

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.