



Product Description

MachFlex™ 350YP Control Cable, 19 Conductor 2.5 mm² Stranded Bare Copper, PVC Insulation, PUR Outer Jacket

Technical Specifications

Product Overview

Construction Details

Conductor

Element	No. of Elements	Size	Stranding	Stranding Class	Material
Conductor(s)	19	2.5 mm ²	Stranded	Class 5	BC - Bare Copper

Insulation

Element	Material	Color Code
		Black #1, Black #2, Black #3, Black #4, Black #5, Black #6, Black #7, Black #8, Black #9, Black #10, Black #11, Black #12, Black #13, Black #14, Black #15, Black #16, Black #17, Black #18, Black #19

Outer Jacket

Material PUR - Polyurethane	
Overall Cable Diameter (Nominal):	18.3 mm (0.720 in)

Electrical Characteristics

Voltage

Voltage Rating
300 / 500 V (Max. Operating Voltage), 4000 V (Testing Voltage)

Mechanical Characteristics

Temperature		
Operatin	ıg	Installation
-20°C to +70°C (Occasi	onal movement)	-40°C to +80°C (Fixed installation)
Bend Radius		
Installation Min. Flo	exing Min.	
73.2 mm (2.88 in) 183	mm (7.20 in)	
Bulk Cable Weight:	629 kg/km (423	lbs/1000ft)
Standards and Co	ompliance	
	Simpliance	
Environmental Suitability:	Sunlight Resista	ance, UV Resistance, Oil Resistance
ISO/IEC Compliance:	IEC 60228	

European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), REACH, EU Directive 2011/65/EU (RoHS 2)
Other Standard Compliance(s):	EN 50525-2-51, VDE 0285, VDE 0295, EN 50363-3, EN 50363-10-2, BS 6360
Product Notes	
Notes:	General Reference Standards : VDE 0207-363-3, DIN VDE 0207-363-10-2
History	

Update and Revision: Revision Number: 0.19 Revision Date: 01-16-2024

Part Numbers

Variants

ltem #	Color	Length
19X2.5P 010100M	Black	100 m
19X2.5P 010200M	Black	200 m
19X2.5P 010300M	Black	300 m
19X2.5P 006100M	Blue	100 m
19X2.5P 006200M	Blue	200 m
19X2.5P 006300M	Blue	300 m
19X2.5P G8U100M	Gray, RAL 7001	100 m
19X2.5P G8U200M	Gray, RAL 7001	200 m
19X2.5P G8U300M	Gray, RAL 7001	300 m

© 2025 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.