

# **Product:** <u>20X0.75P</u> ⊠ MachFlex™ 350YP, 20C 0.75 mm² Str BC, PVC Ins, PUR Outer Jkt

## **Product Description**

MachFlex™ 350YP Control Cable, 20 Conductor 0.75 mm² Stranded Bare Copper, PVC Insulation, PUR Outer Jacket

## **Technical Specifications**

## **Product Overview**

## **Construction Details**

#### Conductor

ĺ	Element	No. of Elements	Size	Stranding	Stranding Class	Material
ĺ	Conductor(s)	20	0.75 mm <sup>2</sup>	Stranded	Class 5	BC - Bare Copper

#### Insulation

Element	Material	Color Code
		Black #1, Black #2, Black #3, Black #4, Black #5, Black #6, Black #7, Black #8, Black #9, Black #10, Black #11, Black #12, Black #13, Black #14, Black #15, Black #16, Black #17, Black #18, Black #18, Black #19, Black #20

#### Outer Jacket

Material	
PUR - Polyurethane	
Overall Cable Diameter (Nominal):	12.8 mm (0.504 in)

## **Electrical Characteristics**

# Voltage

Voltage Rating			
	300 / 500 V (Max. Operating Voltage), 4000 V (Testing Voltage)		

## **Mechanical Characteristics**

Temperature			
Operati	ing Installation		
-20°C to +70°C (Occas	sional movement) -40°C to +80°C (Fixed installation)		
Bend Radius			
Installation Min. F	Flexing Min.		
51.2 mm (2.02 in) 128	3 mm (5.04 in)		
Bulk Cable Weight:	248 kg/km (167 lbs/1000ft)		
Standards and Compliance			
Environmental Suitability:			
ISO/IEC Compliance:	IEC 60228		

European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), REACH, EU Directive 2011/65/EU (RoHS 2)	
Other Standard Compliance(s):	EN 50525-2-51, VDE 0285, VDE 0295, EN 50363-3, EN 50363-10-2, BS 6360	
Product Notes		
Notes:	General Reference Standards : VDE 0207-363-3, DIN VDE 0207-363-10-2	

# History

Update and Revision: Revision Number: 0.19 Revision Date: 01-16-2024

#### **Part Numbers**

#### Variants

ltem #	Color	Length
20X0.75P 010100M	Black	100 m
20X0.75P 010200M	Black	200 m
20X0.75P 010300M	Black	300 m
20X0.75P 006100M	Blue	100 m
20X0.75P 006200M	Blue	200 m
20X0.75P 006300M	Blue	300 m
20X0.75P G8U100M	Gray, RAL 7001	100 m
20X0.75P G8U200M	Gray, RAL 7001	200 m
20X0.75P G8U300M	Gray, RAL 7001	300 m

#### © 2025 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.