



# Product: 2128T

Fieldbus, 2 Pr #16 Str TC, XLPO Ins, IS/OS, LSZH Jkt, 600V TC-ER

## **Product Description**

Fieldbus, 2 Pair 16AWG (7x24H) Tinned Copper, XLPO Insulation, Individual & Overall Beldfoil® Shield, LSZH Outer Jacket, 600V TC-ER

## **Technical Specifications**

### **Product Overview**

Suitable Applications:	harsh environment digital and serial two-way communication, oil and gas extraction and refining sites, petrochemical, Profibus process automation or Foundation FieldBus process automation, extreme temperature environments, exposure to humidity/moisture, dust, and oil, remote locations long distance applications, etc.					
Physical Characteristics (Overall)						
Conductor						

	AWG	Stranding	waterial					
	16	7x24	TC - Tinned Copper					
1	Insulation							
A								

XLPE - Cross-Linked Polyethylene (Thermoset)

Outer Jacket

Material LSZH - Low Smoke Zero Halogen (Flame Retardant)

## Plenum/Non-Plenum

Plenum (Y/N): No

### **Related Part Numbers**

Variants				
Item #	Color	UPC		
2128T 0105000	Black	612825130062		

#### History

Update and Revision:	Revision Number: 0.142 Revision Date: 02-03-2025
-------------------------	--

© 2025 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.