



Product: [2139A](#)

Category 5e Indoor/Outdoor Cable, 25 Pair, F/UTP, OSP/CM-LS, LSZH, CAT Armor

Product Description

Category 5e Premise Backbone Cable (100MHz), Indoor/Outdoor OSP/CM-LS, 25 Pair, 24 AWG Solid Bare Copper Conductors, U/UTP, Gel-Filled, Corrugated Aluminum Tape Armor, UV Resistant Flame Retardant Haloarrest® LSZH Outer Jacket

Technical Specifications

Product Overview

Suitable Applications:	OSP-Outdoor, Indoor/Outdoor, Premise Backbone Cable, Gigabit Ethernet, 100BaseTX, 100BaseVG ANYLAN, 155ATM, 622ATM, NTSC/PAL Component or Composite Video, AES/EBU Digital Audio, AES51, RS-422, Noisy Environments
------------------------	---

Construction Details

Conductor

Size	Stranding	Material	Number of Pairs
24	Solid	BC - Bare Copper	25

Insulation

Material	Color Code
PO - Polyolefin	Western Electric

Inner Jacket

Material	Nom. Diameter	Ripcord
PE - Polyethylene	0.51 in (13 mm)	Yes

Armor

Armor Type & Material	Armor Thickness
CAT - Corrugated Aluminum Tape	.008 in (0.20 mm)

Outer Jacket

Material	Nom. Diameter	Ripcord
LSZH - Low Smoke Zero Halogen (Flame Retardant)	0.730 in (18.5 mm)	Yes

Overall Cable Diameter (Nominal):	0.730 in (18.5 mm)
-----------------------------------	--------------------

Electrical Characteristics

Electricals

Max. Conductor DCR	Max. Capacitance Unbalance
93.8 Ohm/km (28.6 Ohm/1000ft)	330 pF/100m

Delay

Frequency	Max. Delay	Max. Delay Skew	Nom. Velocity of Prop.
100 MHz	537.6 ns/100m	45 ns/100m	68%

High Frequency

Frequency [MHz]	Max. Insertion Loss (Attenuation)	Min. PSNEXT [dB]	Min. RL (Return Loss) [dB]	Max./Min. Fitted Impedance
1	2.0 dB/100m	62.3	20.0	100 ± 15%
4	4.1 dB/100m	53.3	23.0	100 ± 15%

8	5.8 dB/100m	48.8	24.5	100 ± 15%
10	6.5 dB/100m	47.3	25.0	100 ± 15%
16	8.2 dB/100m	44.3	25.0	100 ± 15%
20	9.3 dB/100m	42.8	25.0	100 ± 15%
25	10.4 dB/100m	41.3	24.3	100 ± 15%
31.25	11.7 dB/100m	39.9	23.6	100 ± 15%
62.5	17.0 dB/100m	35.4	21.5	100 ± 15%
100	22.0 dB/100m	32.3	20.1	100 ± 15%

Voltage

UL Voltage Rating
300 V (CM)

Mechanical Characteristics

Temperature

UL Temperature	Operating	Installation	Storage
75°C	-40°C To +75°C	-20°C To +75°C	-40°C To +75°C

Bend Radius

Stationary Min.	Installation Min.
7.5 in (190 mm)	14.75 in (374.7 mm)

Max. Pull Tension:	150 lbs (68 kg)
Bulk Cable Weight:	240 lbs/1000ft

Standards and Compliance

Environmental Suitability:	Indoor/Outdoor, Indoor, Outdoor, Sunlight Resistance
Flammability / Reaction to Fire:	UL 1685 (UL Loading-Limited Smoke)
NEC / UL Compliance:	CM
CEC / C(UL) Compliance:	CM
IEEE Compliance:	IEEE 802.3bt Type 1, Type 2, Type 3
Data Category:	Category 5e
TIA/EIA Compliance:	ANSI/TIA-568.2-D Category 5e
ISO/IEC Compliance:	11801 ed 2.2 (2011) Class D
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE), REACH: 2017-07-10
APAC Compliance:	China RoHS II (GB/T 26572-2011)
Other Standard Compliance(s):	Outdoor Use ANSI/ICEA S56434, Broadband Outdoor Use ANSI/ICEA S99689, Indoor/Outdoor Use ANSI/ICEA S100685

Product Notes

Notes:	Electrical values are expected performance based on cable testing and representative performance within a typical Belden system. Print Includes Descending Footage Markings. Not Suitable for Direct Burial.
--------	--

History

Update and Revision:	Revision Number: 0.329 Revision Date: 05-04-2022
----------------------	--

Part Numbers

Variants

Item #	Color	UPC
2139A 0101000	Black	612825377870

© 2022 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.