



Product: [2147A](#)

Category 6A Indoor/Outdoor Cable, 4 Pair, U/UTP, OSP/CM-LS, LSZH

Product Description

Category 6A Premise Horizontal Cable (500 MHz), Indoor/Outdoor OSP/CM-LS, 4 Pair, 23 AWG Solid Bare Copper Conductors, U/UTP, Haloarrest® LSZH Inner Jacket, Gel-Filled, UV Resistant Flame Retardant Haloarrest® LSZH Outer Jacket

Technical Specifications

Product Overview

Suitable Applications:	OSP-Outdoor, Indoor/Outdoor, Premise Horizontal Cable, Ethernet up to 10GBASE-T, Wi-Fi 6, Wi-Fi 5, PoE++, PoE+, PoE, HDBaseT
Patent:	This product has one or more applicable patents. More information on patents can be found at https://www.belden.com/resources/patents .

Construction Details

Conductor

AWG	Stranding	Material	Number of Pairs
23	Solid	BC - Bare Copper	4

Insulation

Material	Color Code
PO - Polyolefin	White & Blue, White & Orange, White & Green, White & Brown

Bonded-Pair: No

Inner Jacket Material

Material	Nom. Diameter	Ripcord
PE - Polyethylene	0.270 in	No

Waterblocking: Gel Filled

Outer Jacket Material

Separator Material	Material	Material Trade Name	Nom. Diameter	Ripcord
Center Member (Patented X-Spline®)	LSZH - Low Smoke Zero Halogen (Flame Retardant)	Haloarrest®	0.370 in	Yes

Electrical Characteristics

Electricals

Max. Conductor DCR	Max. DCR Unbalance	Max. DCR Unbalanced Between Pairs [%]	Max. Capacitance Unbalance	Nom. Mutual Capacitance
82 Ohm/km	3.0%	5.0%	45 pF/100m	17 pF/ft

Delay

Frequency [MHz]	Max. Delay	Max. Delay Skew	Nom. Velocity of Propagation (VP) [%]
100 MHz	537.6 ns/100m	45 ns/100m	64%

High Freq

Frequency [MHz]	Max. Insertion Loss (Attenuation)	Min. NEXT [dB]	Min. PSNEXT [dB]	Min. ACR [dB]	Min. PSACR [dB]	Min. ACRF (ELFEXT) [dB]	Min. PSACRF (PSELFEXT) [dB]	Min. RL (Return Loss) [dB]	Max./Min. Input Impedance (unFitted)	Max./Min. Fitted Impedance	Min. PSANEXT	Min. PSAACRF	Min. TCL [dB]	Min. ELTCTL [dB]
1 MHz	2.1 dB/100m	74.3 dB	72.3 dB	72.2 dB	70.2 dB	67.8 dB	64.8 dB	20.0 dB	100 +/- 5	115 +/- 15	67.0 dB	67.0 dB	40.0 dB	35.0 dB
4 MHz	3.8 dB/100m	65.3 dB	63.3 dB	61.5 dB	59.5 dB	55.8 dB	52.8 dB	23.0 dB	100 +/- 5	100 +/- 7	67.0 dB	66.2 dB	40.0 dB	23.0 dB

8 MHz	5.3 dB/100m	60.8 dB	58.8 dB	55.4 dB	53.4 dB	49.7 dB	46.7 dB	24.5 dB	100+/- 22	100 +/- 7	67.0 dB	60.1 dB	40.0 dB	16.9 dB
10 MHz	5.9 dB/100m	59.3 dB	57.3 dB	53.4 dB	51.4 dB	47.8 dB	44.8 dB	25.0 dB	100+/- 22	100 +/- 7	67.0 dB	58.2 dB	40.0 dB	15.0 dB
16 MHz	7.5 dB/100m	56.2 dB	54.2 dB	48.8 dB	46.8 dB	43.7 dB	40.7 dB	25.0 dB	100+/- 22	100 +/- 7	67.0 dB	54.1 dB	38.0 dB	10.9 dB
20 MHz	8.4 dB/100m	54.8 dB	52.8 dB	46.4 dB	44.4 dB	41.8 dB	38.8 dB	25.0 dB	100+/- 22	100 +/- 7	67.0 dB	52.2 dB	37.0 dB	9.0 dB
25 MHz	9.4 dB/100m	53.3 dB	51.3 dB	44.0 dB	42.0 dB	39.8 dB	36.8 dB	24.3 dB	100+/- 22	100 +/- 7	67.0 dB	50.2 dB	36.0 dB	7.0 dB
31.25 MHz	10.5 dB/100m	51.9 dB	49.9 dB	41.4 dB	39.4 dB	37.9 dB	34.9 dB	23.6 dB	100+/- 22	100 +/- 7	67.0 dB	48.3 dB	35.1 dB	5.1 dB
62.5 MHz	15.0 dB/100m	47.4 dB	45.4 dB	32.4 dB	30.4 dB	31.9 dB	28.9 dB	21.5 dB	100+/- 22	100 +/- 7	65.6 dB	42.3 dB	32.0 dB	
100 MHz	19.1 dB/100m	44.3 dB	42.3 dB	25.2 dB	23.2 dB	27.8 dB	24.8 dB	20.1 dB	100+/- 22	100 +/- 7	62.5 dB	38.2 dB	30.0 dB	
200 MHz	27.6 dB/100m	39.8 dB	37.8 dB	12.2 dB	10.2 dB	21.8 dB	18.8 dB	18.0 dB	100+/- 22	100 +/- 7	58.0 dB	32.2 dB	27.0 dB	
250 MHz	31.1 dB/100m	38.3 dB	36.3 dB	7.3 dB	5.3 dB	19.8 dB	16.8 dB	17.3 dB	100 +/- 32	100 +/- 7	56.5 dB	30.2 dB	26.0 dB	
300 MHz	34.3 dB/100m	37.1 dB	35.1 dB	2.9 dB	0.9 dB	18.3 dB	15.3 dB	16.8 dB	100 +/- 32	100 +/- 7	55.3 dB	28.7 dB	25.2 dB	
350 MHz	37.2 dB/100m	36.1 dB	34.1 dB			16.9 dB	13.9 dB	16.3 dB	100 +/- 32	100 +/- 7	54.3 dB	27.3 dB	24.6 dB	
400 MHz	40.1 dB/100m	35.3 dB	33.3 dB			15.8 dB	12.8 dB	15.9 dB	100 +/- 32	100 +/- 7	53.5 dB	26.2 dB	24.0 dB	
450 MHz	42.7 dB/100m	34.5 dB	32.5 dB			14.7 dB	11.7 dB	15.5 dB	100 +/- 32	100 +/- 7	52.7 dB	25.1 dB	23.5 dB	
500 MHz	45.3 dB/100m	33.8 dB	31.8 dB			13.8 dB	10.8 dB	15.2 dB	100 +/- 32	100 +/- 7	52.0 dB	24.2 dB	23.0 dB	

Voltage

UL Voltage Rating
300 V (CM-LS)

Mechanical Characteristics

Temperature

UL Rating	Operating	Installation	Storage
75°C	-40°C To +75°C	-20°C To +75°C	-40°C To +75°C

Bend Radius

Stationary Min.	Installation Min.
3.0 in	3.75 in

Max. Pull Tension:	25 lbs
Bulk Cable Weight:	66 lbs/1000ft

Standards and Compliance

Environmental Suitability:	Indoor/Outdoor, Indoor, Outdoor, Non-Halogenated, Sunlight Resistance
Flammability / Fire Resistance:	UL 1685 (UL Loading-Limited Smoke)
NEC / UL Compliance:	Article 800, CM-LS
CEC / C(UL) Compliance:	CM-LS
ICEA Compliance:	S-116-732-2013
ICEA Compliance:	S-56-434
ICEA Compliance:	S-99-689
ICEA Compliance:	S-100-685
IEEE Compliance:	IEEE 802.3bt Type 1, Type 2, Type 3, Type 4
NEMA Compliance:	ANSI/NEMA WC-66
Data Category:	Category 6A
TIA/EIA Compliance:	ANSI/TIA-568.2-D Category 6A
CENELEC Compliance:	Segregation class according EN50174-2=a
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE), REACH: 2020-01-16
APAC Compliance:	China RoHS II (GB/T 26572-2011)
Other Standard Compliance(s):	Verified Channel/Category 6A

Part Number

Variants

Item #	Color	UPC
2147A 0101000	Black	612825379485

Product Notes

Notes:	Electrical values are expected performance based on cable testing and representative performance within a typical Belden system. Print Includes Descending Footage/Meter Markings from Max. Put-Up Length to 0. Not Suitable for Direct Burial.
--------	---

History

Update and Revision:	Revision Number: 0.202 Revision Date: 03-16-2021
----------------------	--

© 2021 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.