



Product: [25372](#) 

XTRAGUARD 2, 2PR #18, Str, PVC, 300 V, AWM/STYLE 20668 90C, VW-1, AWM/STYLE 1569 105C, CSA C(RU) AWM I/II A/B, CSA FT1

Product Description

XTRAGUARD 2, 2 Pair 18 AWG (16/30) TC - Tinned Copper, PVC Insulation, Overall Aluminum/Polyester Shield, Slate Polyurethane (TPU) Outer Jacket, AWM/STYLE 20668 90C, VW-1, AWM/STYLE 1569 105C, CSA C(RU) AWM I/II A/B, CSA FT1 C(RU) AWM I/II A/B, FT1 UL FT1, VW-1; CSA FT1

Technical Specifications

Product Overview

Suitable Applications:	Data, communication, audio, and low-level signal transmission; industrial networking, serial communication, control panels, automation equipment, and instrumentation systems.
------------------------	--

Construction Details

Conductor

Element	No. of Elements	Size	Stranding	Material
Pair(s)	2	18 AWG	16x30	TC - Tinned Copper

Insulation

Element	Material	Nom. Thickness	Nom. Insulation Diameter	Color Code
Pair(s)	PVC - Polyvinyl Chloride	0.016 in (0.41 mm)	0.079 in (2.0 mm)	Black-Red, Black-White

Outer Shield

Shield Type	Material	Coverage	Drainwire Type
Tape	Bi-Laminate (Alum+Poly)	100%	18 AWG (16x30) TC

Outer Jacket

Material	Nom. Thickness	Nom. Diameter	Ripcord
PUR - Polyurethane	0.032 in (0.81 mm)	0.331 in (8.41 mm)	Yes

Overall Cable Diameter (Nominal):	0.331 in (8.41 mm)
-----------------------------------	--------------------

Electrical Characteristics

Electricals

Element	Nom. Capacitance Cond-to-Cond	Nom. Capacitance Cond-to-Other (Conds + Shield)	Nom. Characteristic Impedence	Nom. Inductance
Pair(s)	40 pF/ft (130 pF/m)	72 pF/ft (240 pF/m)	49 Ohm	0.18 µH/ft (0.59 µH/m)

Nom Outer Shield DCR:	56 Ohm/1000ft (180 Ohm/km)
-----------------------	----------------------------

Voltage

UL Voltage Rating	Voltage Rating
300 V (AWM 20668)	300 V (CSA AWM)

Mechanical Characteristics

Temperature

UL Temperature	Operating
105°C	-30°C To +90°C

Bend Radius

Stationary Min.

3.3 in (84 mm)

Max. Pull Tension: 79 lbs (36 kg)

Standards and Compliance

Environmental Suitability:	Indoor, Outdoor
Sustainability:	CA Prop 65
Flammability / Reaction to Fire:	UL1685 FT1 Loading, FT1
AWM Compliance:	AWM 20668, AWM I/II A/B
European Directive Compliance:	EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
UK Regulation Compliance:	UKCA Mark
APAC Compliance:	China RoHS II (GB/T 26572-2011)

Product Notes

Notes: Alpha Wire -* P/N 25372 2PR 18 AWG XTRAGUARD(R) 2 RU AWM 20668 VW-1 OR CRU AWM I/II A/B 90C 300 VOLTS FT1 CE ROHS (SEQ FOOTAGE)

History

Update and Revision: Revision Number: 0.114 Revision Date: 06-30-2026

Part Numbers**Variants**

Item #	Color	Putup Type	Length
25372 BK005	Black and Red	Reel	100 ft

© 2026 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.