



Product: [29525](#)

VFD, 3C #6 Str TC XLPE Ins + #12 Symm. Seg. Gnd (3 of #12) Str BC, CTS, Bik PVC Jkt, 600/1000V TC-ER 90C Dry/Wet 1000V CSA AWM I/II A/B

[Request Sample](#)

Product Description

Belden Premium VFD, 6 AWG (7 x 19 x 27) Tinned Copper, 3 Conductor, XLPE Insulation M4 Color Code, With 3 #12 AWG (65 x 30) Bare Copper Drain Wire, Overall Copper Tape Applied Shield, Black Outer PVC Jacket, 600/1000V TC-ER 90C Dry/Wet 1000V, CSA AWM I/II A/B Sun Res Dir Bur Oil Resistant.

Technical Specifications

Product Overview

Suitable Applications:	Variable Frequency Drives (VFD); AC Motor and Drive Systems; Class 1 Division 2 Hazardous Locations; Recommended Cable Gland Belden BTC125A1041RA
------------------------	---------------------------------------------------------------------------------------------------------------------------------------------------

Construction Details

Conductor

Element	No. of Elements	Size	Stranding	Material	Notes
Conductor(s)	3	6 AWG	7x19x27	TC - Tinned Copper	ASTM B3 Copper B8 Class B Stranding
Segmented Ground Wire	3	12 AWG	65x30	BC - Bare Copper	Segmented Grounds (3 Totaling 6 AWG)

Insulation

Element	Material	Nom. Thickness	Nom. Insulation Diameter	Color Code
Conductor(s)	XLPE - Cross-Linked Polyethylene (Thermoset)	0.047 in (1.2 mm)	0.289 in (7.34 mm)	ICEA Chart M4
Ground Wire	No Insulation			

Outer Shield

Shield Type	Material	Coverage	Notes
Tape	Bare Copper (BC)	100%	2 mil Copper Tape
	Bare Copper (BC)		

Outer Jacket

Material	Nom. Thickness	Nom. Diameter	Ripcord
XLPE - Cross-Linked Polyethylene (Thermoset)	0.063 in (1.6 mm)	0.759 in (19.3 mm)	Yes

Overall Cable Diameter (Nominal): 0.759 in (19.3 mm)

Electrical Characteristics

Electricals

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Nom. Capacitance Cond-to-Other (Conds + Shield)	Nom. Characteristic Impedance	Nom. Velocity of Prop.	Max. Current
Conductor(s)	0.355 Ohm/1000ft (1.16 Ohm/km)	32 pF/ft (100 pF/m)	63 pF/ft (210 pF/m)	37 Ohm	55%	75 Amps per Conductor at 30°C
	0.056 Ohm/1000ft (0.18 Ohm/km)					

Voltage

UL Voltage Rating
600/1000 V (TC-ER)

Mechanical Characteristics

Temperature

UL Temperature	Operating
90°C Dry, 90°C Wet	-20°C To +90°C

Bend Radius

Stationary Min.	Installation Min.
5.69 in (145 mm)	5.69 in (145 mm)

Max. Pull Tension:	1304.1 lbs (591.53 kg)
Bulk Cable Weight:	461 lbs/1000ft (686 kg/km)

Standards and Compliance

Environmental Suitability:	Outdoor, Sunlight Resistance, Burial
Sustainability:	CA Prop 65
Flammability / Reaction to Fire:	UL 1685 UL Loading, IEEE 1202 FT4, FT4
NEC / UL Compliance:	Article 336, TC-ER, XHHW-2
ICEA Compliance:	S-95-658
European Directive Compliance:	EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)
Other Standard Compliance(s):	P-07-KA070003-MSHA

History

Update and Revision:	Revision Number: 0.25 Revision Date: 05-05-2025
----------------------	-------------------------------------------------

© 2025 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.