



Product: [3119A](#)

DeviceBus® for InterBus®-S, 3 Pr #18+24 Str TC, PVC+PO Ins, OS+TC Brd, PUR Jkt, AWM 20233

[Request Sample](#)

Product Description

DeviceBus® for InterBus®-S, 3 Pair 18+24AWG (7x26+7x32) Tinned Copper, PVC+PO Insulation, Overall Beldfoil®+Tinned Copper Braid(90%) Shield, PUR Outer Jacket, AWM 20233

Technical Specifications

Product Overview

Suitable Applications:	harsh environment, IIoT, factory or process automation, video, audio, data communication, etc.
------------------------	------------------------------------------------------------------------------------------------

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	No. of Conductors	No. of Pairs
24	7x32	TC - Tinned Copper		3
18		TC - Tinned Copper	3	

Conductor Count:	9
------------------	---

Insulation

Material	Nominal Wall Thickness
PE - Polyethylene	0.016 in
PVC - Polyvinyl Chloride	0.01 in

Color Chart

Number	Color
1	White & Brown
2	Pink & Gray
3	Green & Yellow
4	
5	
6	

Color Chart 2

Color
Red
Blue
Yellow/Green

Outer Shield Material

Type	Layer	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Tape	1	Bi-Laminate (Alum+Poly)	Beldfoil®	100%	TC - Tinned Copper	24	7x32
Braid	2	Tinned Copper (TC)		90%			

Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness
PUR - Polyurethane	0.333 in	0.035 in

Electrical Characteristics

Conductor DCR

Element	Nominal Conductor DCR	Nominal Outer Shield DCR
24	23.4 Ohm/1000ft	2.7 Ohm/1000ft
	6.6 Ohm/1000ft	

Capacitance

Nom. Capacitance Conductor to Shield
15.4 pF/ft
15.4 pF/ft

Impedance

Nominal Characteristic Impedance
100 Ohm
100 Ohm

Delay

Nominal Velocity of Propagation (VP) Description
24 AWG

Current

Element	Max. Recommended Current [A]
24 AWG	2.1 Amps per Conductor
18 AWG	4.8 Amps per Conductor

Voltage

UL Description	UL Voltage Rating
	UL AWM 20233
300 V	

Temperature Range

UL Temp Rating:	80°C
Operating Temp Range:	-40°C to +80°C

Mechanical Characteristics

Oil Resistance:	Yes
Bulk Cable Weight:	62 lbs/1000ft
Max. Pull Tension:	100 lbs
Min. Bend Radius/Minor Axis:	3 in

Standards

UL AWM Style Compliance:	20233
CPR Euroclass:	Eca

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2011/65/EU (RoHS 2):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU (RoHS 2 amendment):	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-10-01
MII Order #39 (China RoHS):	Yes

Suitability

Suitability - Sunlight Resistance:	Yes
------------------------------------	-----

Flammability, LS0H, Toxicity Testing

IEC Flammability:	IEC 60332-1-2
UL voltage rating:	300 V RMS (UL AWM Style 20233)

Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

Part Number

Variants

Item #	Color	Putup Type	Length	UPC
3119A Y5P500	Green Y5P	Reel	500 ft	612825141976
3119A Y5P1000	Green Y5P	Reel	1,000 ft	612825141969

Footnote:	C - CRATE REEL PUT-UP.
-----------	------------------------

History

Update and Revision:	Revision Number: 0.308 Revision Date: 05-26-2021
----------------------	--------------------------------------------------

© 2021 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.