

# Product: <u>32P2016</u> ☑ Inst PVC/PVC, 16 Pr #20 Str BC, PVC Ins E1, Blk PVC Jkt, 300V PLTC ITC CMG

# **Product Description**

UL Instrumentation, 16 Pair 20AWG (7x28) Bare Copper, PVC Insulation E1 Color Code, Black PVC Outer Jacket, PLTC ITC CMG AWM 2464 SUN RES

# **Technical Specifications**

## **Product Overview**

Suitable Applications:	Industrial Control, Raceways Cable trays and ducts, Digital Control, Instruments (4-20ma, 0-10v,), low voltage digital control (24v,), RTD, control circuits, distributed control system (DCS), programmable logic controller (PLC), Solenoids, Valves, actuators, positioners
onstruction Detai	ls
onductor	
Element No. of Elemen	ts Size Stranding Material
Pair(s) 16	20 AWG 7x28 BC - Bare Copper
sulation	
Element Materia	al Nom. Thickness Nom. Insulation Diameter Color Code
Pair(s) PVC - Polyviny	I Chloride 0.0175 in (0.445 mm) 0.071 in (1.8 mm) Black & White and Numbered
nner Shield	
Element Shield Type	Material Coverage Drainwire Type
Pair(s) Tape I	Bi-Laminate (Alum+Poly) 100% 24 AWG (7x32) TC
uter Shield	
	aterial Coverage Drainwire Type
	e (Alum+Poly) 100% 24 AWG (7x32) TC
Outer Jacket	
Material	Nom. Thickness Nom. Diameter Ripcord   0.063 in (1.6 mm) 0.706 in Yes
Overall Cable Diameter	0.706 in
(Nominal):	
Electrical Characte	ristics
lectricals	
Nom. Conductor DCR	Nom. Inner Shield DCR Max. Current
10.7 Ohm/1000ft	18.3 Ohm/1000ft (60.0 Ohm/km) 2.5 Amps per Conductor at 25°C

# Voltage

UL Voltage Rating

300 V

**Mechanical Characteristics** 

Temperature
-------------

UL Temperature	Operating	
UL: 105°C, AWM 2464: 80°C	-20°C to +105°C	

#### Bend Radius

Stationary Min.	Installation	n Min.
7.06 in (179 mm)	7.06 in	
Max. Pull Tension	n: 4!	496 lbs
Bulk Cable Weigh	nt: 2	276 lbs/

## **Standards and Compliance**

Indoor, Outdoor, Sunlight Resistance				
UL1685 FT4 Loading, FT4, T-29-520, IEEE 1202 FT4				
Article 725, Article 727, Article 800				
AWM 2464				
CMG				
EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)				
China RoHS II (GB/T 26572-2011)				

## History

Update and Revision:	Revision Number: 0.50 Revision Date: 05-31-2024

### **Part Numbers**

Variants						
	ltem #	UPC				
	32P2016 0105000	612825360902				

## © 2025 Belden, Inc All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.