



# Product: <u>3G35SY</u> I

MachFlex<sup>™</sup> 350SY, 2C+1G 35 mm<sup>2</sup> Str BC, PVC Ins, PVC Inner Jkt, GSW Brd, PVC Outer Jkt

# **Product Description**

MachFlex<sup>™</sup> 350SY VDE Certified, 2 Conductor + 1 Ground 35 mm<sup>2</sup> Stranded Bare Copper, PVC Insulation, PVC Inner Jacket, Galvanized Steel Wire Braid, PVC Outer Jacket Control Cable

# **Technical Specifications**

# **Product Overview**

Suitable Applications:	Application for occasional flexing or fixed installation connecting precision control sensors, multi axis control machines, temperature controllers, control panels, machine cutting tools, auxiliary equipment, motor speed control, production machinery and many morein hash industrial environment.

# **Construction Details**

#### Conductor

Element	No. of Elements	Size	Stranding	Stranding Class	Material
Conductor(s)	2	35 mm²	Stranded	Class 5	BC - Bare Copper
Ground	1	35 mm <sup>2</sup>	Stranded	Class 5	BC - Bare Copper

#### Insulation

Element	Material	Color Code
Conductor(s)	PVC - Polyvinyl Chloride	Black #1, Black #2
Ground	PVC - Polyvinyl Chloride	Yellow/Green

# Inner Jacket

Material PVC - Polyvinyl Chloride

#### Armor

Armor Type & Material SWB - Steel Wire Braid Armor

#### Outer Jacket

Material PVC - Polyvinyl Chloride	
Overall Cable Diameter (Nominal):	28.5 mm (1.12 in)

## **Electrical Characteristics**

#### Voltage

Voltage Rating 300 / 500 V (Max. Operating Voltage)

### **Mechanical Characteristics**

#### Temperature

Operating	Installation
-15°C to +70°C (Occasional movement)	-40°C to +80°C(Fixed installation)

#### Bend Radius

Installation Min.Flexing Min.171 mm (6.73 in)570 mm (22 in)

Bulk Cable Weight: 1673 kg/km (1124 lbs/1000ft)

### **Standards and Compliance**

Environmental Suitability:	Indoor, Outdoor, Oil Resistance - EN 50290-2-22 (TM54), Oil Resistance
Flammability / Reaction to Fire:	IEC 60332-1-2, DIN VDE 048233212
Third Party Performance Verification:	VDE Certification No. 40041970, VDE Registration No. 8770
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2)
APAC Compliance:	China RoHS II (GB/T 26572-2011)
Other Standard Compliance(s):	VDE 0285-525-2-51, EN 50525-2-51, IEC 60227-5

#### **History**

Variants

Update and Revision: Revision Number: 0.26 Revision Date: 03-19-2024

# **Part Numbers**

#### ltem # Color Length 3G35SY 010100M Black, RAL 9004 100 m 3G35SY 010200M Black, RAL 9004 200 m 3G35SY 010300M Black, RAL 9004 300 m 3G35SY G8U100M Gray, RAL 7001 100 m 3G35SY G8U200M Gray, RAL 7001 200 m 3G35SY G8U300M Gray, RAL 7001 300 m 3G35SY 368100M Transparent 100 m Transparent 3G35SY 368200M 200 m 3G35SY 368300M Transparent 300 m

#### © 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or guality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.