



**Product:** [4000UE](#)

Security & Sound, 2 Conductor 12 AWG BC, LSZH, Eca

**Product Description**

Security & Commercial Audio Cable, 2-12 AWG stranded bare copper conductors with polypropylene insulation, LSZH jacket with ripcord, CPR Eca

**Technical Specifications**

**Product Overview**

Suitable Applications:	Commercial applications
------------------------	-------------------------

**Physical Characteristics (Overall)**

Conductor				
AWG	Stranding	Material	Nominal Diameter	No. of Conductors
12	19x25	BC - Bare Copper	2.3 mm	2
Conductor Count:				2

Insulation				
Type	Material	Nominal Diameter	Diameter +/- Tolerance	Nominal Wall Thickness
Insulation	PP - Polypropylene	3 mm	0.05 mm	0.35 mm

Color Chart	
Number	Color
Wire 1	Black
Wire 2	White

Outer Jacket			
Material	Nominal Diameter	Nominal Wall Thickness	Ripcord
LSZH - Low Smoke Zero Halogen (Flame Retardant)	6.8 mm	0.38 mm	Yes
Table Notes:		Ripcord provided under sheath	

**Construction and Dimensions**

Cabling	
Description	2 wires twisted

Electrical Characteristics	
Conductor DCR	
Nominal Conductor DCR	5.2 Ohm/km
Capacitance	
Nom. Capacitance Conductor to Conductor	105 pF/m

Current	
Max. Recommended Current [A]	

12 A
------

Voltage

Voltage Rating [V]
300 V

Temperature Range

Installation Temperature Range:	-20°C To +70°C
Storage Temperature Range:	-30°C To +70°C
Operating Temperature Range:	-20°C To +70°C

Mechanical Characteristics

Max. Pull Tension:	70 N
Min. Bend Radius During Installation:	68 mm
Min Setting Radius:	34 mm

Standards

CPR Euroclass:	Eca
----------------	-----

Applicable Environmental and Other Programs

Environmental Space:	Indoor - Euroclass Eca
----------------------	------------------------

Flammability, LSOH, Toxicity Testing

IEC Flammability:	IEC 60332-1-2
IEC 60754-1 - Halogen Amount:	Zero
IEC 60754-2 - Halogen Acid Gas Amount - Max. Conductivity:	2.5 µS/mm
IEC 60754-2 - Halogen Acid Gas Amount - Min. pH:	4.3
IEC 61034-2 - Smoke Density Min. Transmittance:	60%

Related Part Numbers

Variants

Item #	Color	Put-Up Type	Length	EAN
4000UE.00100	Gray	Reel	100 m	8719605006165
4000UE.00500	Gray	Reel	500 m	8719605006172

History

Update and Revision:	Revision Number: 0.222 Revision Date: 02-15-2024
----------------------	--

© 2024 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.