


Product: [413945](#) 



Surveillance CCTV, RG-11 #14 BC, 95% BC Braid, LSZH Jkt.

Product Description

Surveillance & CCTV Cable, RG11, Rated-CM, 14 AWG solid bare copper, foam polyolefin core, 95% bare copper braid, LSZH jacket, IEC 60332-1

Technical Specifications

Product Overview

Suitable Applications:	ANALOG VIDEO/CCTV; The cable is suitable for indoor use
------------------------	---

Construction Details

RG Type:	11
----------	----

Conductor

Number of Element	Size	Stranding	Nom. Diameter	Material
1	14 AWG	Solid	1.6 mm	BC - Bare Copper

Insulation

Material	Nom. Insulation Diameter
PE - Polyethylene (Foam)	7.11 mm (0.280 in)

Outer Shield

Outer Shield Type	Material	Coverage
Braid	Bare Copper (BC)	95%

Outer Jacket

Material	Nom. Diameter
LSZH - Low Smoke Zero Halogen (Flame Retardant)	10.3 mm

Electrical Characteristics

Attenuation

Frequency	Nom. Attenuation
1 MHz	0.56 dB/100m
10 MHz	1.15 dB/100m
50 MHz	2.95 dB/100m
100 MHz	4.26 dB/100m
200 MHz	6.23 dB/100m
400 MHz	9.5 dB/100m
700 MHz	13.4 dB/100m
900 MHz	15.7 dB/100m
1000 MHz	17 dB/100m

Electricals

Nom. Conductor DCR	Nom. Outer Shield DCR	Nom. Capacitance Cond-to-Shield	Nom. Characteristic Impedance	Nom. Velocity of Prop.
8.5 Ohm/km	4.7 Ohm/km (1.4 Ohm/1000ft)	52.8 pF/m (16.1 pF/ft)	75 Ohm	84%

Voltage

Voltage Rating

300 V RMS

Mechanical Characteristics

Temperature

Operating	Storage
-30°C To +70°C	-30°C To +70°C

Bend Radius

Stationary Min.	Installation Min.
51.5 mm (2.03 in)	103 mm

Max. Pull Tension:	65 N (15 lbf)
Bulk Cable Weight:	124 kg/km

Standards and Compliance

Environmental Suitability:	Indoor
Flammability / Reaction to Fire:	IEC 60332-1-2
CPR Compliance:	CPR Euroclass: Eca
European Halogen Free Standards:	IEC 62821-1 Halogen Free Compliance = Yes, IEC 60754-1 - Halogen Amount = Zero, IEC 60754-2 - Halogen Acid Gas Amount - Max. Conductivity = 2.5 µS/mm, IEC 60754-2 - Halogen Acid Gas Amount - Min. pH = 4.3

History

Update and Revision:	Revision Number: 0.208 Revision Date: 04-08-2022
----------------------	--

Part Numbers

Variants

Item #	Color	Putup Type	Length	EAN
413945.01500	Black	Reel	500 m	8719605170392
413945.00305	Gray	Reel	305 m	8719605006271
413945.00500	Gray	Reel	500 m	8719605006288

© 2022 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.