



Product: <u>4303FE</u> ☑

Security & Sound, 5 Conductor18 AWG BC twisted cable, LSZH, Shielded, Eca

Product Description

Security & Commercial Audio Cable, 5 twisted 18 AWG stranded bare copper conductors with polypropylene insulation , Beldfoil® shield, LSZH jacket with ripcord, CPR Eca

Technical Specifications

Product Overview

Product O	verview						
Suitable Appl	lications: Security System, Intercom/PA, Audio/Speaker, Power-Limited Controls, Noisy Environment						
Construct	ion Details						
Conductor							
Size Strand							
18 7x26	18 7x26 BC - Bare Copper						
Insulation							
Materia				lation Diameter	Color Co		
PP - Polyprop	oylene 0.2 mm (0	.0079 in)	1.5 mm (0.0	059 in)	Black, Red, White, C	Green, Brown	
Outer Shield							
Shield Type	Materia		Coverage	Drainwire Typ	e		
Таре	Bi-Laminate (Alu	m+Poly)	100%	24 AWG (7x32)	тс		
Outer Jacket							
	Material			Nom. Thicknes	s Nom. Diameter	Ripcord	

Material	Nom. Thickness	Nom. Diameter	Ripcord	
LSZH - Low Smoke Zero Halo	gen (Flame Retardant)	0.4 mm (0.016 in)	5.4 mm (0.21 in)	Yes
Table Notes: Ripcord provided un		der sheath		
Overall Cable Diameter (Nominal):	5.4 mm (0.21 in)			

Electrical Characteristics

Electricals

Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Nom. Capacitance Cond-to-Other (Conds + Shield)	Max. Current
21.3 Ohm/km (6.49 Ohm/1000ft)	125 pF/m (38.1 pF/ft)	224 pF/m (68.3 pF/ft)	3.5 Amps per Conductor

Mechanical Characteristics

Temperature		
Operating	Installation	Storage
-20°C To +70°C	-20°C To +70°C	-30°C To +70°C
Bend Radius		
Installation Min.		
54 mm (2.1 in)		
Max. Pull Tensior	ı: 21	0 N (47 lbf)

Standards and Compliance

Environmental Suitability:	Indoor - Euroclass Eca, Non-Halogenated
Flammability / Reaction to Fire:	IEC 60332-1-2
CPR Compliance:	CPR Euroclass: Eca
ISO/IEC Compliance:	IEC 61034-2 - Smoke Density Min Transmittance = 60%
CENELEC Compliance:	EN 50290-2-20
European Halogen Free Standards:	IEC 62821-1 Halogen Free Compliance = Yes, IEC 60754-1 - Halogen Amount = Zero, IEC 60754-2 - Halogen Acid Gas Amount - Max. Conductivity = 2.5 µS/mm, IEC 60754-2 - Halogen Acid Gas Amount - Min. pH = 4.3
European Directive Compliance:	EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2)
UK Regulation Compliance:	UKCA Mark

History

Update and Revision: Revision Number: 0.39 Revision Date: 06-28-2024

Part Numbers

Variants

Item # 4303FE.00500

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.