



Product: [438AMJ](#)

Life Cycle Status: Capability

Access Control, 16c (#18-3pr, #16-4c, #18-6c), Only Card Reader Pairs Shielded, Outer Jacket, Eca

Product Description

Access Control Cable, 3-18 AWG pairs, 4-16 AWG conductors, 4-18 AWG conductors, 2-18 AWG conductors, All conductors stranded bare copper with polyolefin insulation, Only Card Reader pairs have overall Beldfoil® shield and LSZH jackets, Overall LSZH jacket

Technical Specifications

Product Overview

Suitable Applications:	Access Control, Security System, Power Limited Controls
------------------------	---

Construction Details

Conductor

Element Description	Element	No. of Elements	Size	Stranding	Material
Card Reader	Pair(s)	3	18 AWG	7x26	BC - Bare Copper
Door Contact	Conductor(s)	2	18 AWG	7x26	BC - Bare Copper
REX/Spare	Conductor(s)	4	18 AWG	7x26	BC - Bare Copper
Lock Power	Conductor(s)	4	16 AWG	19x29	BC - Bare Copper

Insulation

Element Description	Element	Material	Nom. Insulation Diameter	Color Code
Card Reader	Pair(s)	PP - Polypropylene		Black & Red, White & Green, Brown & Orange
Door Contact	Conductor(s)	PP - Polypropylene		Black, Red
REX/Spare	Conductor(s)	PP - Polypropylene		Black, Red, White, Green
Lock Power	Conductor(s)	PP - Polypropylene	0.073 in (1.9 mm)	

Inner Shield

Element Description	Element	Shield Type	Material	Coverage	Drainwire Type
Card Reader	Pair(s)	Tape	Bi-Laminate (Alum+Poly)	100%	24 AWG (7x32) TC
Door Contact	Conductor(s)	No Shield			
REX/Spare	Conductor(s)	No Shield			
Lock Power	Conductor(s)	No Shield			

Inner Jacket

Element Description	Element	Material	Nom. Diameter	Ripcord	Color
Card Reader	Pair(s)	LSZH - Low Smoke Zero Halogen (Flame Retardant)	0.272 in (6.91 mm)	Yes	Orange
Door Contact	Conductor(s)	LSZH - Low Smoke Zero Halogen (Flame Retardant)	0.158 in (4.01 mm)	Yes	White
REX/Spare	Conductor(s)	LSZH - Low Smoke Zero Halogen (Flame Retardant)	0.184 in (4.67 mm)	Yes	Blue
Lock Power	Conductor(s)	LSZH - Low Smoke Zero Halogen (Flame Retardant)	0.210 in (5.33 mm)	Yes	Gray

Outer Jacket

Nom. Diameter	Ripcord
0.570 in (14.5 mm)	Yes

Overall Cable Diameter (Nominal):	0.570 in (14.5 mm)
-----------------------------------	--------------------

Electrical Characteristics

Electricals

Element Description	Element	Nom. Conductor DCR	Nom. Inner Shield DCR	Nom. Capacitance Cond-to-Cond	Nom. Capacitance Cond-to-Shield	Max. Current
Card Reader	Pair(s)		13.1 Ohm/1000ft (43.0 Ohm/km)	29 pF/ft (95 pF/m)	52.25 pF/ft (171.4 pF/m)	4 Amps per Conductor at 25°C
Door Contact	Conductor(s)	6.6 Ohm/1000ft (22 Ohm/km)				4 Amps per Conductor at 25°C
REX/Spare	Conductor(s)	6.6 Ohm/1000ft (22 Ohm/km)				4 Amps per Conductor at 25°C
Lock Power	Conductor(s)	4 Ohm/1000ft (13 Ohm/km)				5 Amps per Conductor at 25°C

Mechanical Characteristics

Temperature

Operating
-5°C to +70°C

Max. Pull Tension:	235 lbs (107 kg)
--------------------	------------------

Standards and Compliance

Environmental Suitability:	Indoor
CPR Compliance:	CPR Euroclass: Eca
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2)
APAC Compliance:	China RoHS II (GB/T 26572-2011)
Plenum Number:	638AMJ

Product Notes

Notes:	This is a preliminary Technical Design Specification (TDS) which is subject to modification throughout the prototyping phase. The minimum business quantity to offer is 3km for the first order. This product will have Yellow as standard color and 305mt as standard put-ups. Additional options for colors and put-ups are available on special request. The estimated production lead time for the first order needs to be requested to a Belden Representative.
--------	--

History

Update and Revision:	Revision Number: 0.6 Revision Date: 06-19-2024
----------------------	--

© 2025 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.