


Product: [5102UP](#) 



Audio Cable, 4 Conductor 14 AWG, BC, Unshielded, CM

Product Description

Commercial Audio Cable, Rated-CL3, 4-14 AWG highly flexible stranded bare copper conductors with PVC insulation, PVC jacket with ripcord

Technical Specifications

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	No. of Conductors
14	42x30	BC - Bare Copper	4

Conductor Count:

Insulation

Material	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.02 in

Color Chart

Color
Black
White
Red
Green

Outer Shield Material

Material
No Shield

Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness	Ripcord
PVC - Polyvinyl Chloride	0.313 in	0.018 in	Yes

Construction and Dimensions

Cabling

Twists
2.8 twist/ft

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR
2.42 Ohm/1000ft

Capacitance

Nom. Capacitance Conductor to Conductor
29 pF/ft

Inductance

Nominal Inductance

0.17 µH/ft

Current

Max. Recommended Current [A]

17.6 Amps per Conductor at 25°C

Voltage

UL Voltage Rating

300 V RMS

Temperature Range

UL Temp Rating:	75°C
Operating Temp Range:	-20°C To +75°C

Mechanical Characteristics

Bulk Cable Weight:	76 lbs/1000ft
Max. Pull Tension:	218.4 lbs
Min Bend Radius/Minor Axis:	3 in

Standards

NEC/(UL) Compliance:	CL3
----------------------	-----

Applicable Environmental and Other Programs

Environmental Space:	Indoor (Not Riser or Plenum)
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
MII Order #39 (China RoHS):	Yes

Flammability, LSOH, Toxicity Testing

UL Flammability:	UL1685 UL Loading
UL voltage rating:	300 V RMS

Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

Part Number

Variants

Item #	Color	Putup Type	Length	UPC
5102UP 010500	Black	Reel	500 ft	612825156727
5102UP D15500	Blue	Reel	500 ft	612825156161
5102UP D151000	Blue	Reel	1,000 ft	612825156734
5102UP 008500	Gray	Reel	500 ft	612825156765
5102UP 0081000	Gray	Reel	1,000 ft	612825156758
5102UP 005500	Green, Dark	Reel	500 ft	612825156741
5102UP 009500	White	Reel	500 ft	612825156772
5102UP 0101000	White	Reel	1,000 ft	612825156789

Footnote: C - CRATE REEL PUT-UP.

History

Update and Revision:	Revision Number: 0.258 Revision Date: 06-24-2020
----------------------	--

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.