

Product: <u>5140F1</u> ☑ Security & Sound, #14-1pr, TC, Shielded, CL3-FPL-PLTC-ER, Water-Blocked

Product Description

Security & Sound Cable, Rated-CL3-FPL-PLTC, 1-14 AWG stranded tinned copper pair with PVC insulation, Beldfoil® shield, Waterblocking tape, PVC jacket

Technical Specifications

Product Overview

Suitable Applications:	Security System, Intercom/PA, Audio/Speaker, Fire Alarm (Red Jkt), Power-Limited Controls, Noisy & Wet Location, Below-Grade Duct
Construction Details	
Construction Details	
Conductor	
Element No. of Elements	Size Stranding Material
Pair(s) 1 14	4 AWG 19x26 TC - Tinned Copper
Insulation	
Element Material	Nom. Thickness Nom. Insulation Diameter Color Code
Pair(s) PVC - Polyvinyl Chlo	bride 0.014 in (0.36 mm) 0.104 in (2.64 mm) Black & Red
Outer Shield	
Shield Type Materia	I Coverage Drainwire Type
Tape Bi-Laminate (Alu	um+Poly) 100% 16 AWG (19x29) TC
Waterblocking:	Waterblock Tape
Outer Jacket	
Material Nom	n. Thickness Nom. Diameter
PVC - Polyvinyl Chloride 0.04	2 in (1.1 mm) 0.326 in (8.28 mm)
Overall Cable Diameter (Nomin	nal): 0.326 in (8.28 mm)
Electrical Characterist	ics
Electricals	
Element Nom. Conductor De	
Pair(s) 3.05 Ohm/1000ft	83 pF/ft (270 pF/m) 29 Amps per conductor @ 30°C
Voltage	
UL Voltage Rating	
300 V (CL3, FPL, PLTC-ER)	
Mechanical Characteri	stics

Temperature

UL Temperature	Operating
105°C	-20°C to +105°C

Bend Radius

Stationary Min.	Installation Min
3.3 in (84 mm)	3.3 in (84 mm)

Max. Pull Tension:	135 lbs (61.2 kg)
Bulk Cable Weight:	61 lbs/1000ft

Standards and Compliance

Environmental Suitability:	Indoor/Outdoor, Indoor, Outdoor, Sunlight Resistance, Burial		
Sustainability:	Product Lens™, Environmental Product Declaration (EPD) Available		
Flammability / Reaction to Fire:	UL 1685 FT4 Loading, FT4, IEEE 1202 FT4, IEC 60332-1-2		
CPR Compliance:	CPR Euroclass: Eca		
NEC / UL Compliance:	Article 725, Article 760, Article 800, CL3, FPL, PLTC		
CEC / C(UL) Compliance:	CL3		
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)		
UK Regulation Compliance:	UKCA Mark		
APAC Compliance:	China RoHS II (GB/T 26572-2011)		

History

Update and Revision: Revision Number: 0.447 Revision Date: 02-03-2025

Part Numbers

Variants								
	Item #	Color	UPC	Fo				
	5140F1 0101000	Black	612825157151	С				

© 2025 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or guality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.