



Product: [5302F2](#)

Security & Sound, #18-4c BC, Shielded, CL3, FPL, PLTC, Water-Blocked Direct Burial

Product Description
Security & Sound Cable, Rated-CL3, 4-18 AWG PVC-Nylon insulation,100% Shielded, Waterblocking tape, PVC jacket with ripcord

Technical Specifications

Product Overview

Suitable Applications:	Security System, Intercom/PA, Audio/Speaker, Power-Limited Controls, Wet Location, Direct Burial
------------------------	--

Construction Details

Conductor				
Element	No. of Elements	Size	Stranding	Material
Conductor(s)	4	18 AWG	7x26	BC - Bare Copper

Insulation				
Material	Nom. Thickness	Nom. Insulation Diameter	Color Code	
PVC/Nylon - Polyvinyl Chloride + Nylon	.020 in (0.51 mm)	.020 in (0.51 mm)	Black, Red, Blue, Brown	

Outer Shield				
Shield Type	Material	Coverage	Drainwire Type	Notes
Tape	Bi-Laminate (Alum+Poly)	100%	24 AWG (7x32) TC	100% Waterblocking Tape

Waterblocking:	Waterblock Tape
----------------	-----------------

Outer Jacket				
Material	Nom. Thickness	Nom. Diameter	Ripcord	
PVC - Polyvinyl Chloride	.040 in (1.0 mm)	.371 in (9.42 mm)	Yes	

Electrical Characteristics

Electricals			
Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Nom. Capacitance Cond-to-Other (Conds + Shield)	
6.2 Ohm/1000ft (20 Ohm/km)	32 pF/ft (100 pF/m)	58 pF/ft (190 pF/m)	

Voltage	
UL Voltage Rating	
300 V RMS	

Mechanical Characteristics

Temperature	
UL Temperature	Operating
90°C	-20°C To +90°C

Bend Radius	
Stationary Min.	Installation Min.
3.34 in (84.8 mm)	3.34 in (84.8 mm)

Max. Pull Tension:	112 lbs (50.8 kg)
--------------------	-------------------

Bulk Cable Weight:	60 lbs (27 kg)
--------------------	----------------

Standards and Compliance

Environmental Suitability:	Outdoor - Direct Burial, Indoor, Outdoor, Sunlight Resistance, Burial
Sustainability:	CA Prop 65
Flammability / Reaction to Fire:	UL 1685
CPR Compliance:	CPR Euroclass: Eca
NEC / UL Compliance:	Article 725, Article 760, CL3, FPL, PLTC
CEC / C(UL) Compliance:	CL3
TIA/EIA Compliance:	TIA455-82 Water Penetration Test
European Directive Compliance:	EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
UK Regulation Compliance:	UKCA Mark
APAC Compliance:	China RoHS II (GB/T 26572-2011)

History

Update and Revision:	Revision Number: 0.5 Revision Date: 07-10-2025
----------------------	--

© 2025 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.