



Product Description

Security & Sound Cable, Rated-CM, 2-20 AWG stranded tinned copper conductors with PVC insulation, waterblocking tape, Beldfoil® shield and PVC jacket with ripcord

Technical Specifications

Product Overview

Suitable Applications:		Secur	Security System, Intercom/PA, Audio/Speaker, Power-Limited Controls, Noisy & Wet Location, Below-Grade Duct					
Constructi	ion Details							
Conductor								
Element	No. of Elements	Size	Stranding	Material				
Conductor(s)	2	20 AWG	i 7x28	TC - Tinned Copper				
nsulation								
Element	Material	ł	Nom. Thickn	ess Nom. Insulation	Diameter Color Code			
Conductor(s)	PVC - Polyvinyl C	hloride ().01 in (0.25 r	nm) 0.058 in (1.5 mm) Black, Red			
Shield Type Tape	Material Bi-Laminate (Alum			Drainwire Type 2 AWG (7x30) TC				
Waterblocking	g:	Water	block Tape					
Outer Jacket								
Separato	or Ma	terial	Nom.	Thickness Nom. Di	ameter Ripcord			
Waterblocking	g Tape PVC - Poly	vinyl Chlo	oride 0.025 i	n (0.64 mm) 0.197 in	Yes			
Overall Cable	Diameter (Nominal): 0.197	in					
	Characteristic	5						
Electricals								
	Nom. Conductor	DCR N	om, Capacita	ince Cond-to-Cond	Nom. Capacitance Cond-to-Other (Conds + Shie	ld) Max. Current		
Element	Nom. Conductor							

Voltage

UL Voltage Rating 300 V

Mechanical Characteristics

UL Temperature	Operating
105°C	-40°C To +105°C

Bend Radius

Stationary Min. Installation Min.

1.97 in (50.0 mm) 1.97 in	
Max. Pull Tension:	34 lbs (15 kg)
Bulk Cable Weight:	19 lbs/1000ft

Standards and Compliance

Environmental Suitability:	Indoor, Outdoor, Sunlight Resistance
Sustainability:	Product Lens™, Environmental Product Declaration (EPD) Available
Flammability / Reaction to Fire:	UL1685 UL Loading
NEC / UL Compliance:	Article 800, CM
CEC / C(UL) Compliance:	CM
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)

History

Update and Revision: Revision Number: 0.305 Revision Date: 02-03-2025

Part Numbers

Variants

Item #	Color	UPC	Footnote
5400F1 0081000	Gray	612825161974	С

© 2025 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or guality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.