



Product: <u>5X6SY</u> 2

MachFlex[™] 350SY, 5C 6 mm² Str BC, PVC Ins, PVC Inner Jkt, GSW Brd, PVC Outer Jkt

Product Description

MachFlex™ 350SY VDE Certified, 5 Conductor 6 mm² Stranded Bare Copper, PVC Insulation, PVC Inner Jacket, Galvanized Steel Wire Braid, PVC Outer Jacket Control Cable

Technical Specifications

Product Overview

Suitable Applications:					g precision control sensors, multi axis control machines, temperature controllers, control panels, machine cut chinery and many morein hash industrial environment.
Construction Details					
Conductor					
Element No. of Elem	onts Size	Stranding	Stranding Class	Material	
Conductor(s) 5	6 mm²	Stranded	Class 5	BC - Bare Copper	
nsulation					
Element Mate	rial		Color Code		
Conductor(s) PVC - Polyv	nyl Chloride	Black #1, Bl	ack #2, Black #3, I	Black #4, Black #5	
nner Jacket					
Material					
PVC - Polyvinyl Chloride					
Armor					
Armor Type & Material SWB - Steel Wire Braid Arn	or				
SWD - Steel Wire Blaid All					
Outer Jacket					
Material					
PVC - Polyvinyl Chloride					
Overall Cable Diameter (Nominal):	17.7 mm (0	.697 in)			
Electrical Character	stics				
/oltage					
Voltage Rating 300 / 500 V (Max, Operating	Mathematic				

300 / 500 V (Max. Operating Voltage)

Mechanical Characteristics

Temperature

Operating	Installation
-15°C to +70°C (Occasional movement)	-40°C to +80°C(Fixed installation)

Bend Radius

Installation Min. Flexing Min.

106.2 mm (4.181 in) 354 mm (13.9 in)

Bulk Cable Weight: 607 kg/km (408 lbs/1000ft)

Standards and Compliance

Environmental Suitability:	Indoor, Outdoor, Oil Resistance - EN 50290-2-22 (TM54), Oil Resistance				
Flammability / Reaction to Fire:	IEC 60332-1-2, DIN VDE 048233212				
Third Party Performance Verification:	VDE Certification No. 40041970, VDE Registration No. 8770				
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2)				
APAC Compliance:	China RoHS II (GB/T 26572-2011)				
Other Standard Compliance(s):	VDE 0285-525-2-51, EN 50525-2-51, IEC 60227-5				

History

Update and Revision: Revision Number: 0.27 Revision Date: 03-19-2024

Part Numbers

Variants

ltem #	Color	Length
5X6SY 010100M	Black, RAL 9004	100 m
5X6SY 010200M	Black, RAL 9004	200 m
5X6SY 010300M	Black, RAL 9004	300 m
5X6SY G8U100M	Gray, RAL 7001	100 m
5X6SY G8U200M	Gray, RAL 7001	200 m
5X6SY G8U300M	Gray, RAL 7001	300 m
5X6SY 368100M	Transparent	100 m
5X6SY 368200M	Transparent	200 m
5X6SY 368300M	Transparent	300 m

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.