



Product: 6002UH ☑

Security & Sound, 4 Conductor 12 AWG TC, CL2P

# **Product Description**

Security & Commercial Audio Cable, 4 Conductor 12 AWG stranded (19x25) tinned copper conductors with Flamarrest® insulation, plenum CL2P rating and Flamarrest® low smoke PVC jacket with ripcord.

## **Technical Specifications**

### **Product Overview**

Suitable Applications:	Intercom/PA Systems, Sound/Audio Systems
Physical Characteristics (Overall)	

#### Conductor

AWG	Stranding	Material	Nominal Diameter	No. of Conductors
12	19x25	TC - Tinned Copper	0.091 in	4
Condu	ctor Count:		4	

## Insulation

Material	Material Trade Name	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	Flamarrest®	0.111 in	0.010 in

### Color Chart



### Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.304 in	0.018 in

# **Electrical Characteristics**

### Conductor DCR

Nominal Conductor DCR
1.6 Ohm/1000ft

#### Capacitance



#### Current

Max. Recommended Current [A]
9.6 Amps per Conductor

## Voltage



## **Temperature Range**

UL Temp Rating:	75°C
Operating Temp Range:	0°C To +75°C

## **Mechanical Characteristics**

UV Resistance:	No
Bulk Cable Weight:	102 lbs/1000ft
Max. Pull Tension:	304 lbs
Min Bend Radius/Minor Axis:	3.25 in

#### **Standards**

NEC/(UL) Compliance:	CL2P
(- / -	

### **Applicable Environmental and Other Programs**

Environmental Space:	Indoor - Plenum
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/11/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01

### **Suitability**

Suitability - Aerial:	No
Suitability - Burial:	No
Suitability - Hazardous Locations:	No
Suitability - Indoor:	Yes
Suitability - Outdoor:	No
Suitability - Sunlight Resistance:	No

# Flammability, LS0H, Toxicity Testing

C(UL) Flammability:	FT6
UL Flammability:	NFPA 262
UL voltage rating:	150 V RMS

### Plenum/Non-Plenum

Plenum (Y/N):	Yes

### **Part Number**

Non-Plenum Number:	5002UH

### Variants

Item #	Color	Putup Type	Length	UPC
6002UH 8771000	Natural	Reel	1,000 ft	611589228190

## **History**

Update and Revision:	Revision Number: 0.51 Revision Date: 02-16-2021

© 2021 Belden, Inc

All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief

at the date of its publication. This information is d Disclosure is not to be considered a warranty or or regulations based on their individual usage of the	esigned only as a general guide for the sat yuality specification. Regulatory information product.	fe handling, storage, and any othen n is for guidance purposes only. Pr	r operation of the product itself or tr oduct users are responsible for det	ne one that it becomes a part of. T ermining the applicability of legisla	ne Product ition and