



**Product:** [6054](#)

Teck90 600V, 3+3+G C #12+14+14 Str BC, XLPE Ins, PVC Jkt, AIA Armor, Bk PVC Jkt, CSA HL SUN RES -40C

## Product Description

Teck90 600V, 3+3+G Conductor 12+14+14AWG (7x20H+7x22H) Bare Copper, XLPE Insulation, PVC Inner Jacket, Aluminum Interlock Armor, Black PVC Outer Jacket, CSA HL SUN RES -40C

## Technical Specifications

### Product Overview

Suitable Applications:	Power and Control Applications up to 600V
------------------------	---

### Construction Details

#### Conductor

Element	Number of Element	Size	Stranding	Material
Conductor1	3	12 AWG	7x20	BC - Bare Copper
Conductor2	3	14 AWG	7x22	BC - Bare Copper
Ground Wire	1	14 AWG	7x22	BC - Bare Copper

#### Insulation

Element	Material	Nom. Thickness	Nom. Insulation Diameter	Color Code
Conductor1	XLP, XLPO, XLPE (Thermoset)	0.03 in (0.76 mm)	0.150 in (3.81 mm)	ICEA Chart E2
Conductor2	XLP, XLPO, XLPE (Thermoset)	0.03 in (0.76 mm)	0.132 in (3.35 mm)	ICEA Chart E2
Ground Wire	No Insulation			

#### Outer Shield

Material
No Shield

#### Inner Jacket

Material	Nom. Thickness	Nom. Diameter	Ripcord	Color
PVC - Polyvinyl Chloride	0.047 in (1.2 mm)	0.518 in (13.2 mm)	Yes	Black

#### Armor

Armor Type & Material	Armor Thickness	Diameter Over Armor
AIA - Aluminum Interlock Armor	0.025 in (0.64 mm)	0.743 in (18.9 mm)

#### Outer Jacket

Material	Nom. Thickness	Nom. Diameter
PVC - Polyvinyl Chloride	0.048 in (1.2 mm)	0.839 in

Overall Cable Diameter (Nominal):	0.839 in
-----------------------------------	----------

## Electrical Characteristics

### Electricals

Element	Nom. Conductor DCR	Max. Current
Conductor(s)	1.68 Ohm/1000ft	24 Amps per Conductor at 30°C
Conductor(s)	2.7 Ohm/1000ft (8.9 Ohm/km)	25 Amps per Conductor at 30°C
Ground Wire	2.65 Ohm/1000ft (8.69 Ohm/km)	

## Voltage

### Voltage Rating

600 V (TECK 90)

## Mechanical Characteristics

### Temperature

#### Operating

-40°C To +90°C

### Bend Radius

Stationary Min.	Installation Min.
-----------------	-------------------

6.712 in (170.5 mm)	6.712 in
---------------------	----------

Max. Pull Tension:	679 lbs (308 kg)
--------------------	------------------

Bulk Cable Weight:	348 lbs/1000ft
--------------------	----------------

## Standards and Compliance

Environmental Suitability:	Indoor, Outdoor, Sunlight Resistance, UV Resistance
----------------------------	---

Flammability / Reaction to Fire:	FT4
----------------------------------	-----

CEC / C(UL) Compliance:	TECK 90, HL
-------------------------	-------------

## History

Update and Revision:	Revision Number: 0.185 Revision Date: 07-15-2022
----------------------	--

## Part Numbers

### Variants

Item #	Putup Type	UPC
6054 0105000	Reel	612825339045

© 2022 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.