


Product: [70001E](#) 

Profibus PA, 1PR #18 Str TC, PO ins, F/B, PVC jkt, 300 V



Product Description

Profibus PA, 1 Pair AWG 18 Tinned Copper - Stranded, Polyolefin (PO, PE, PP) insulation, Foil + Braid(s) shielding, PVC jacket , 300 V

Technical Specifications

Product Overview

Suitable Applications:	Profibus PA or Foundation FieldBus PA
------------------------	---------------------------------------

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	No. of Pairs
18	7x26	TC - Tinned Copper	1

Conductor Count:	2
Total Number of Pairs:	1

Insulation

Material	Nominal Diameter	Diameter +/- Tolerance	Nominal Wall Thickness
PE - Polyethylene (Foam)	2.5 mm	0.05 mm	0.65 mm

Color Chart

Number	Color
Pair 1	Red & Green

Outer Shield

Type	Material	Thickness of Foil	Drainwire Material	Drainwire AWG	Drainwire Position	Min. Coverage [%]
Tape	Bi-Laminate (Alum+Poly)	9 / 23 µm	TC - Tinned Copper	AWG20/7	In contact with tape and braid	
Braid	Tinned Copper (TC)					85%

Outer Jacket

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	8 mm	1.15 mm

Construction and Dimensions

Cabling

Description	Filler
1 pair and 2 fillers twisted to cable core	Polyethylene (2x) (1.65 mm)

Electrical Characteristics

Conductor DCR

Max. Conductor DCR	Max. Outer Shield DCR
20.5 Ohm/km	9 Ohm/km

Capacitance

Max. Capacitance Conductor to Conductor	Max. Capacitance Unbalance
80 pF/m	4 pF/m

Impedance

Frequency [MHz]	Nominal Characteristic Impedance	Nominal Characteristic Tolerance
0.03125 MHz	100 Ohm	20 Ohm

High Frequency (Nominal/Typical)

Frequency [MHz]	Nom. Insertion Loss
0.039 MHz	0.3 dB/100m

Delay

Nominal Velocity of Propagation (VP) [%]
77%

Voltage

Voltage Rating [V]
300 V

Temperature Range

Installation Temperature Range:	-15°C To +75°C
Storage Temperature Range:	-45°C To +75°C
Operating Temp Range (Flexible Install):	-15°C To +75°C
Operating Temp Range (Fixed Install):	-45°C To +75°C

Mechanical Characteristics

Oil Resistance:	IEC 60811-2-1
Max. Pull Tension:	260 N
Min. Bend Radius During Installation:	120 mm
Min Setting Radius:	80 mm

Standards

CPR Euroclass:	Eca
----------------	-----

Applicable Environmental and Other Programs

Environmental Space:	Indoor - Euroclass Eca
----------------------	------------------------

Suitability

Suitability - Oil Resistance:	Yes
Suitability - Sunlight Resistance:	Yes

Flammability, LSOH, Toxicity Testing

IEC Flammability:	IEC 60332-1-2
-------------------	---------------

Related Part Numbers

Variants

Item #	Color	Put-Up Type	Length	EAN
70001E.01120	Black	Reel	120 m	8719605170033
70001E.01500	Black	Reel	500 m	8719605009036

History

Update and Revision:	Revision Number: 0.206 Revision Date: 02-15-2024
----------------------	--

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

