



Product: [70050](#)

1 PAIR AES/EBU, 22AWG, ISTP, LSZH

## Product Description

DIGITAL AUDIO 1 PAIR AES/EBU, 22AWG/0.34mm<sup>2</sup>, ISTP, LSZH

## Technical Specifications

### Product Overview

Suitable Applications:	1-pair 22AWG halogen-free single pair cable; For digital audio
------------------------	--

### Physical Characteristics (Overall)

#### Conductor

AWG	Stranding	Material	Construction n x D
22	7x30	BC-OFHC - Oxygen-Free Bare Copper (High Conductivity)	7x0.25 mm

Conductor Count:	2
Total Number of Pairs:	1

#### Insulation

Type	Material	Nominal Diameter	Diameter +/- Tolerance
Insulation	PE - Polyethylene (Foam)	2.10 mm	0.05 mm

#### Color Chart

Number	Color
Pair 1	Red & Black

#### Outer Shield Material

Type	Material	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D	Drainwire Position
Tape	Bi-Laminate (Alum+Poly)	100%	TC - Tinned Copper	22	7x0.25 mm	Under shielding foil

#### Outer Jacket Material

Material	Nominal Diameter	Diameter +/- Tolerance
LSZH - Low Smoke Zero Halogen (Flame Retardant)	6.00 mm	0.10 mm

### Construction and Dimensions

#### Cabling

Description
1 pair

### Electrical Characteristics

#### Conductor DCR

Nominal Conductor DCR
58.0 Ohm/km

#### Capacitance

Nom. Capacitance Conductor to Conductor

45 pF/m

#### Impedance

Frequency [MHz]	Nominal Characteristic Impedance	Nominal Characteristic Tolerance
0.1 - 6	110 Ohm	+/- 15 Ohm

#### Temperature Range

Other Temp Range:	-30 to +70 °C
-------------------	---------------

#### Mechanical Characteristics

Max. Pull Tension:	70 N
Min Bend Radius During Installation:	60 mm
Min Bend Radius During Operation:	90 mm

#### Standards

CPR Euroclass:	Fca
----------------	-----

#### Applicable Environmental and Other Programs

Environmental Space:	Indoor
EU RoHS Compliance Date (yyyy-mm-dd):	2017-03-02

#### Flammability, LSOH, Toxicity Testing

IEC Flammability:	IEC 60332-1-2
LOI of Jacket:	Min. 34 %
IEC 60754-1 (EN50267-1)- Halogen Amount:	Zero
IEC 60754-2 (EN50267-2)- Halogen Acid Gas Amount - Max. Conductivity:	2.5 µS/mm
IEC 60754-2 (EN50267-2)- Halogen Acid Gas Amount - Min. pH:	4.3

#### Part Number

##### Variants

Item #	Color	Putup Type	Length	EAN
70050.01500	Green	Reel	500 m	8719605125774
70050.00100	Purple	Reel	100 m	8719605159083
70050.00500	Purple	Reel	500 m	8719605010025

#### History

Update and Revision:	Revision Number: 0.148 Revision Date: 09-30-2020
----------------------	--

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.