



REPRESENTATIVE IMAGE

Product: [7500A](#)

MachFlex™, Vision Coax 75Ω, #30 Str Tinned Alloy, FPE Ins, OA TC Brd, PVC Jkt, High Flex, AWM 1354

[Request Sample](#)

Product Description

30AWG (7x38) Tinned Alloy, Foam PE Insulation, Overall Tinned Copper Braid(95%) Shield, PVC Outer Jacket, High Flex, AWM 1354

Technical Specifications

Product Overview

Suitable Applications:	Automation, Robotics, Vision Control
------------------------	--------------------------------------

Construction Details

Conductor

Size	Stranding	Nom. Diameter	Material
30 AWG	7x38	0.012 in	TCA - Tinned Copper Alloy

Insulation

Material	Nom. Insulation Diameter
PE - Polyethylene (Foam)	0.056 in (1.4 mm)

Outer Shield

Outer Shield Type	Material	Coverage
French Braid	Tinned Copper (TC)	95%
	Tinned Copper (TC)	

Outer Jacket

Material	Nom. Diameter
PVC - Polyvinyl Chloride	0.110 in (2.79 mm)

Overall Cable Diameter (Nominal): 0.110 in (2.79 mm)

Electrical Characteristics

Attenuation

Frequency	Nom. Attenuation
2.2 MHz	0.9 dB/100ft
5 MHz	1.4 dB/100ft
10 MHz	2.0 dB/100ft
30 MHz	3.4 dB/100ft
50 MHz	4.4 dB/100ft
100 MHz	6.4 dB/100ft

Electricals

Nom. Conductor DCR	Nom. Outer Shield DCR	Nom. Capacitance Cond-to-Shield	Nom. Characteristic Impedance	Nom. Velocity of Prop.
108 Ohm/1000ft (354 Ohm/km)	13.3 Ohm/1000ft (43.6 Ohm/km)	17.3 pF/ft (56.8 pF/m)	75 Ohm	78%

Voltage

UL Voltage Rating
30 V (UL AWM 1354)

Mechanical Characteristics

Temperature

UL Temperature	Operating
60°C	-35°C to +80°C

Bend Radius

Installation Min.	Flexing Min.
1.1 in	2.2 in (56 mm)

Max. Pull Tension:	11 lbs (5.0 kg)
Bulk Cable Weight:	8 lbs/1000ft

Standards and Compliance

Environmental Suitability:	Indoor (Not Riser or Plenum), Indoor
Sustainability:	CA Prop 65
Flammability / Reaction to Fire:	UL 1581 Horizontal Wire, FT1
AWM Compliance:	1354, AWM I/II A/B
CEC / C(UL) Compliance:	LL7874
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), REACH, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)

History

Update and Revision:	Revision Number: 0.355 Revision Date: 11-15-2021
----------------------	--------------------------------------------------

Variants

Item #	Color	Putup Type	Length	UPC
7500A G7X1000	Blue, Matte	Reel	1,000 ft	612825187202

© 2021 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.