



Product: [75030](#) 

XGIE, 2PR #24, Str, Polyethylene, High Density, 600 V RMS, CM 75C, CMX-Outdoor 75C, SUN RES, AWM/STYLE 2463 80C, CSA C(UL) TYPE CMX-Outdoor

Product Description

XGIE, 2 Pair 24 AWG TC - Tinned Copper, Polyethylene, High Density Insulation, Teal TPE Outer Jacket, CM 75C, CMX-Outdoor 75C, SUN RES, AWM/STYLE 2463 80C, CSA C(UL) TYPE CMX-Outdoor C(UL) TYPE CMX-Outdoor

Technical Specifications

Product Overview

Suitable Applications:	Data, communication, audio, and low-level signal transmission; industrial networking, serial communication, control panels, automation equipment, and instrumentation systems.
------------------------	--

Construction Details

Conductor

Element	Size	Stranding	Material	No. of Pairs
Pair(s)	24 AWG	7x32	TC - Tinned Copper	2

Insulation

Element	Material	Nom. Insulation Diameter	Color Code
Pair(s)	PE - Polyethylene	0.039 in (0.99 mm)	White/Blue & Blue, Orange & White/Orange

Outer Jacket

Material	Nom. Diameter
TPE - Thermoplastic Elastomer	0.240 in (6.10 mm)

Overall Cable Diameter (Nominal):	0.240 in (6.10 mm)
-----------------------------------	--------------------

Electrical Characteristics

Electricals

Element	Max. Conductor DCR	Max. Mutual Capacitance	Max. Capacitance Unbalance	Nom. Characteristic Impedance
Pair(s)	140 Ohm/km (43 Ohm/1000ft)	56 pF/m (17 pF/ft)	330 pF/100m	100 Ohm

Delay

Max. Delay Skew	Nom. Velocity of Prop.
45 ns/100m	66%

High Frequency

Frequency [MHz]	Max. Insertion Loss (Attenuation)	Min. NEXT [dB]	Min. PSNEXT [dB]	Min. ACR [dB]	Min. PSACRF (PSELFEXT) [dB]	Min. RL (Return Loss) [dB]
1	2.4 dB/100m	65.3	62.3	63.8	60.8	20
4	4.9 dB/100m	56.3	53.3	51.8	48.8	23
8	6.9 dB/100m	51.8	48.8	45.7	42.7	24.5
10	7.8 dB/100m	50.3	47.3	43.8	40.8	25
16	9.9 dB/100m	47.2	44.2	39.7	36.7	25
20	11.1 dB/100m	45.8	42.8	37.8	34.8	25
25	12.5 dB/100m	44.3	41.3	35.8	32.8	24.2
31.25	14.1 dB/100m	42.9	39.9	33.9	30.9	23.3
62.5	20.4 dB/100m	38.4	35.4	27.9	24.9	21.7
100	26.4 dB/100m	35.3	32.3	23.8	20.8	19

Mechanical Characteristics

Temperature

UL Temperature	Operating
80°C	-40°C To +80°C

Bend Radius

Stationary Min.	Installation Min.
1.2 in (30 mm)	4.1 in (100 mm)

Max. Pull Tension:	52 lbs (24 kg)
Bulk Cable Weight:	24.5 lbs/1000ft

Standards and Compliance

Environmental Suitability:	Indoor/Outdoor, Indoor, Outdoor, Sunlight Resistance, Oil Resistance
Flammability / Reaction to Fire:	UL 1581 (Vertical Tray), (VW-1)
NEC / UL Compliance:	Article 800, CM, CMX-Outdoor
AWM Compliance:	AWM 2463
CEC / C(UL) Compliance:	CM, CMX-Outdoor
Data Category:	Category 5e
TIA/EIA Compliance:	ANSI/TIA-568.2-D Category 5e
ISO/IEC Compliance:	ISO/IEC 11801 Cat 5e
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
UK Regulation Compliance:	UKCA Mark
APAC Compliance:	China RoHS II (GB/T 26572-2011)

Product Notes

Notes:	ALPHA WIRE-A3 P/N 75030 HIGH FLEX CAT5E UTP 2P 24AWG E163860 C(UL)JUS CMX-OUTDOOR - CM 75C SUN RES OR AWM 2463 80C 600V OIL RES II CE ROHS (SEQ FOOTAGE)
--------	--

History

Update and Revision:	Revision Number: 0.6 Revision Date: 07-08-2026
----------------------	--

Part Numbers

Variants

Item #	Color	Putup Type	Length
75030 TL005	Teal	Reel	100 ft
75030 TL001	Teal	Reel	1,000 ft

© 2026 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.