



**Part Number: 7731A**

Serial Digital Coax, RG11, #14 Solid BC, Foil + 95% TC braid, CMR

**Product Description**

Low Loss Serial Digital Coax, Riser-CMR, RG11 14 AWG solid bare copper conductor, foam HDPE core, Duofoil, +95% tinned copper braid, PVC jacket

**Technical Specifications**

**Product Overview**

Environmental Space:	Outdoor - Aerial
Suitable Applications:	SMPTE 2081-1 6 Gb/s UHDTV, SMPTE 424M 3 Gb/s HD-SDI 1080p

**Physical Characteristics (Overall)**

**Conductor**

AWG	Stranding	Material	Nominal Diameter	No. of Coax
14	Solid	BC - Bare Copper	0.064 in	1

Conductor Count:	1
Conductor Size:	14 AWG

**Insulation**

Material	Nominal Diameter
Gas-injected FHDPE - Foam High Density Polyethylene	0.28 in

**Outer Shield Material**

Type	Layer	Material	Material Trade Name	Coverage [%]
Tape	1	Aluminum/Polyester/Aluminum	Duofoil®	100 %
Braid	2	TC - Tinned Copper		95 %

**Outer Jacket Material**

Material	Nominal Diameter
PVC - Polyvinyl Chloride	0.4 in

**Electrical Characteristics**

**Conductor DCR**

Nominal Conductor DCR	Nominal Outer Shield DCR	Outer Conductor DCR
2.5 Ohm/1000ft	1.5 Ohm/1000ft	1.5 Ohm/1000ft

**Capacitance**

Nom. Capacitance Conductor to Shield
16 pF/ft

**Inductance**

Nominal Inductance
0.097 µH/ft

**Impedance**

Nominal Characteristic Impedance
75 Ohm

#### Return Loss (RL)

Frequency [MHz]	Minimum Return (RL)
5-1600 MHz	23 dB
1600-4500 MHz	21 dB
4500-6000 MHz	15 dB

#### High Frequency (Nominal/Typical)

Frequency [MHz]	Nom. Insertion Loss
1 MHz	0.16 dB/100ft
3.58 MHz	0.29 dB/100ft
5 MHz	0.34 dB/100ft
7 MHz	0.39 dB/100ft
10 MHz	0.46 dB/100ft
67.5 MHz	1.05 dB/100ft
71.5 MHz	1.09 dB/100ft
88.5 MHz	1.21 dB/100ft
100 MHz	1.28 dB/100ft
135 MHz	1.47 dB/100ft
143 MHz	1.51 dB/100ft
180 MHz	1.69 dB/100ft
270 MHz	1.97 dB/100ft
360 MHz	2.31 dB/100ft
540 MHz	2.87 dB/100ft
720 MHz	3.40 dB/100ft
750 MHz	3.45 dB/100ft
1000 MHz	3.60 dB/100ft
1000 MHz	4.12 dB/100ft
1500 MHz	5.10 dB/100ft
2000 MHz	6.04 dB/100ft
2250 MHz	6.43 dB/100ft
3000 MHz	7.63 dB/100ft
4500 MHz	9.56 dB/100ft
6000 MHz	11.53 dB/100ft

#### Delay

Nominal Delay	Nominal Velocity of Propagation (VP) [%]
1.21 ns/ft	85 %

#### Voltage

UL Voltage Rating
300 V RMS

Electrical Characteristics Notes:	TDR Impedance: 75 +/- 3 Ohms
Other Electrical Characteristic 2:	Return Loss: Fixed bridge and termination

#### Temperature Range

UL Temp Rating:	75°C
Operating Temp Range:	-30°C To +75°C

#### Mechanical Characteristics

UV Resistance:	Yes
Bulk Cable Weight:	87 lbs/1000ft
Max Recommended Pulling Tension:	145 lbs
Min Bend Radius/Minor Axis:	4 in

#### Standards

NEC/(UL) Specification:	CMR
CEC/C(UL) Specification:	CMG
CPR Euroclass:	Eca
RG Type:	11/U Type

## Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2004-01-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

## Suitability

Suitability - Aerial:	Yes - Black only, when supported by messenger wire
Suitability - Burial:	No
Suitability - Hazardous Locations:	No
Suitability - Indoor:	Yes
Suitability - Outdoor:	Yes - Black only

## Flammability, LSOH, Toxicity Testing

UL Flammability:	UL1666 Vertical Shaft
CSA Flammability:	FT4
UL voltage rating:	300 V RMS

## Plenum/Non-Plenum

Plenum (Y/N):	No
Plenum Number:	7732A

## Part Number

### Variants

Item #	Color	Footnote
7731A.001220	Black	
7731A.00152	Black	
7731A.002000	Black	
7731A.00305	Black	
7731A 0101000	Black	C
7731A 0104000	Black	C
7731A 010500	Black	C
7731A.031220	Blue	
7731A.03152	Blue	
7731A.03305	Blue	
7731A 0061000	Blue, Light	
7731A 0064000	Blue, Light	C
7731A 0011000	Brown	
7731A 0014000	Brown	C
7731A 0081000	Gray	
7731A 0084000	Gray	C
7731A.081220	Gray, Slate	
7731A.08305	Gray, Slate	
7731A.021220	Green	
7731A.02305	Green	
7731A N3U1000	Green, Mil	C
7731A N3U4000	Green, Mil	C
7731A 0031000	Orange	
7731A 0034000	Orange	C
7731A.061220	Orange, RAL 2003	
7731A.06305	Orange, RAL 2003	
7731A.051220	Purple	

7731A.05305	Purple	
7731A.0021000	Red	C
7731A.0024000	Red	C
7731A.011220	Red, RAL 3000	
7731A.01152	Red, RAL 3000	
7731A.01305	Red, RAL 3000	
7731A.0071000	Violet	C
7731A.0074000	Violet	C
7731A.071220	White	
7731A.07305	White	
7731A.0091000	White	
7731A.0094000	White	C
7731A.0041000	Yellow	
7731A.0044000	Yellow	C
7731A.041220	Yellow, RAL 1021	
7731A.04305	Yellow, RAL 1021	

Footnote:	C - CRATE REEL PUT-UP.
-----------	------------------------

**Product Notes**

Notes:	Print legend includes sequential footage marks.
--------	---

© 2019 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.