



Product: [77905ELW](#)

KNX, 1PR 0.8mm Sol BC, LSZH ins, OS, LSZH Jkt, Cca

Product Description

KNX, 1 Pair, 0.8 mm cond diameter, Bare Copper - Solid, LSZH insulation, Overall Beldfoil® shielding, LSZH / FRNC jacket , CPR Cca

Technical Specifications

Product Overview

Suitable Applications:	KNX, EIB cable for building management
------------------------	--

Physical Characteristics (Overall)

Conductor

Stranding	Material	Nominal Diameter	No. of Pairs
Solid	BC - Bare Copper	0.8 mm	1

Conductor Count:	2
------------------	---

Insulation

Material	Nominal Diameter	Diameter +/- Tolerance	Nominal Wall Thickness
LSZH - Low Smoke Zero Halogen (Flame Retardant)	1.8 mm	0.05 mm	0.5 mm

Color Chart

Number	Color
Pair 1	Red & Blue

Outer Shield

Type	Material Trade Name	Coverage [%]	Thickness of Foil	Drainwire Material	Drainwire Diameter
Tape	Beldfoil®	100%	9 µm	TC - Tinned Copper	0.4 mm

Outer Jacket

Material	Nominal Diameter	Nominal Wall Thickness
LSZH - Low Smoke Zero Halogen (Flame Retardant)	6.60 mm	1.4 mm

Construction and Dimensions

Cabling

Description
1 pair covered with a PP foam foil

Electrical Characteristics

Conductor DCR

Max. Conductor DCR
37.5 Ohm/km

Capacitance

Nom. Capacitance Conductor to Conductor
70 pF/m

Voltage

Voltage Rating [V]

300 V

Electrical Characteristics Notes: Testvoltage 4 kV, 1 min

Temperature Range

Storage Temperature Range: -30°C to +70°C

Operating Temperature Range: -20°C To +70°C

Mechanical Characteristics

Min. Bend Radius During Installation: 66 mm

Min Setting Radius: 33 mm

Standards

CPR Euroclass: Cca-s1,d1,a1

Applicable Environmental and Other Programs

Environmental Space: Indoor - Euroclass Cca

Flammability, LS0H, Toxicity Testing

IEC Flammability: IEC 60332-1-2

IEC 60754-1 - Halogen Amount: Zero

IEC 60754-2 - Halogen Acid Gas Amount - Max. Conductivity: 2.5 µS/mm

IEC 60754-2 - Halogen Acid Gas Amount - Min. pH: 4.3

History

Update and Revision: Revision Number: 0.53 Revision Date: 02-15-2024

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.