



Product: [7810R](#)

50 Ohm Wireless Transmission Coax, RF 400, RG8, 10 AWG Solid BCCA, Foil + 95% TC Braid, PVC Jkt, CMR

Product Description

50 Ohm Wireless Transmission Coax, RF 400, 10 AWG Solid Bare Copper Covered Aluminum, PE Insulation, Duobond® Foil + 95% Tinned Copper Braid Shield, PVC Jacket, CMR

Technical Specifications

Product Overview

| | |
|------------------------|--|
| Suitable Applications: | Point-to-point and point-to-multipoint wireless antenna communication; Wireless microphones, Two-Way Radios, Amateur (Ham) Radio, Low Power FM, GPS, RFID (Radio Frequency Identification) |
|------------------------|--|

Construction Details

Conductor

| No. of Elements | Size | Stranding | Nom. Diameter | Material |
|-----------------|--------|-----------|---------------|-------------------------------------|
| 1 | 10 AWG | Solid | 0.108 in | BCCA - Bare Copper Covered Aluminum |

Insulation

| Material | Nom. Insulation Diameter | Color Code |
|--------------------------|--------------------------|------------|
| PE - Polyethylene (Foam) | 0.285 in (7.24 mm) | White |

| | |
|--------------|--------------|
| Table Notes: | Gas Injected |
|--------------|--------------|

Outer Shield

| Layer | Outer Shield Type | Material | Material Trade Name | Coverage |
|-------|-------------------|-------------------------------|---------------------|----------|
| 1 | Tape | Tri-Laminate (Alum+Poly+Alum) | Duofoil® | 100% |
| 2 | Braid | Tinned Copper (TC) | | 95% |

Outer Jacket

| Material | Nom. Diameter |
|--------------------------|--------------------|
| PVC - Polyvinyl Chloride | 0.403 in (10.2 mm) |

| | |
|-----------------------------------|--------------------|
| Overall Cable Diameter (Nominal): | 0.403 in (10.2 mm) |
|-----------------------------------|--------------------|

Electrical Characteristics

VSWR

| Frequency | Max. VSWR |
|------------|-----------|
| 5-6000 MHz | 1.25:1 |

Attenuation

| Frequency | Nom. Attenuation | Max. Attenuation |
|-----------|------------------|------------------|
| 30 MHz | 0.7 dB/100ft | 0.7 dB/100ft |
| 50 MHz | 0.9 dB/100ft | 0.93 dB/100ft |
| 150 MHz | 1.5 dB/100ft | 1.58 dB/100ft |
| 220 MHz | 1.8 dB/100ft | 1.94 dB/100ft |
| 450 MHz | 2.7 dB/100ft | 2.83 dB/100ft |
| 900 MHz | 3.8 dB/100ft | 4.06 dB/100ft |
| 1500 MHz | 5.1 dB/100ft | 5.32 dB/100ft |

| | | |
|----------|---------------|----------------|
| 1800 MHz | 5.6 dB/100ft | 5.98 dB/100ft |
| 2000 MHz | 6 dB/100ft | 6.35 dB/100ft |
| 2500 MHz | 6.7 dB/100ft | 7.08 dB/100ft |
| 3000 MHz | 7.5 dB/100ft | 7.97 dB/100ft |
| 3500 MHz | 8.2 dB/100ft | 8.8 dB/100ft |
| 4500 MHz | 9.5 dB/100ft | 10.23 dB/100ft |
| 5800 MHz | 11.1 dB/100ft | 12 dB/100ft |
| 6000 MHz | 11.4 dB/100ft | 12.23 dB/100ft |

Power Rating

| Frequency | Max. Power Rating |
|-----------|-------------------|
| 30 MHz | 3,427 W |
| 50 MHz | 2,588 W |
| 150 MHz | 1,428 W |
| 220 MHz | 1,195 W |
| 450 MHz | 817 W |
| 900 MHz | 575 W |
| 1,500 MHz | 437 W |
| 2,000 MHz | 375 W |
| 2,500 MHz | 334 W |
| 3,500 MHz | 282 W |
| 4,500 MHz | 247 W |
| 6,000 MHz | 213 W |
| 4,500 MHz | 247 W |
| 5,800 MHz | 217 W |
| 6,000 MHz | 213 W |

Electricals

| Nom. Conductor DCR | Nom. Outer Shield DCR | Nom. Capacitance Cond-to-Shield | Nom. Characteristic Impedance | Nom. Velocity of Prop. |
|-------------------------------|-----------------------------|---------------------------------|-------------------------------|------------------------|
| 1.34 Ohm/1000ft (4.40 Ohm/km) | 2.0 Ohm/1000ft (6.6 Ohm/km) | 23 pF/ft (75 pF/m) | 50 Ohm | 86% |

Voltage

| Voltage Rating |
|----------------|
| 300 V RMS |

Mechanical Characteristics

Temperature

| UL Temperature | Operating |
|----------------|----------------|
| 60°C | -40°C To +75°C |

Bend Radius

| Stationary Min. | Installation Min. |
|------------------|-------------------|
| 4.00 in (102 mm) | 4.00 in (102 mm) |

| | |
|--------------------|-----------------|
| Max. Pull Tension: | 150 lbs (68 kg) |
| Bulk Cable Weight: | 86 lbs/1000ft |

Standards and Compliance

| | |
|----------------------------------|---|
| Environmental Suitability: | Indoor - Riser, Indoor |
| Flammability / Reaction to Fire: | UL1666 Vertical Shaft, FT4, IEC 60332-1-2 |
| CPR Compliance: | CPR Euroclass: Eca |
| NEC / UL Compliance: | Article 800, CMR |
| CEC / C(UL) Compliance: | CMG |
| European Directive Compliance: | EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE) |
| UK Regulation Compliance: | UKCA Mark |
| APAC Compliance: | China RoHS II (GB/T 26572-2011) |

Product Notes

| | |
|--------|---|
| Notes: | Impedance: 51.0 +/- 2.0 Ohms // PF_7810R (1)RG Type :-In Stibo it was 8 But in BPCS it is not there. (2)# Elements@Conductor1:-In Stibo it was Blank and now changed to 1. (3)Size@Conductor1 :-In Stibo it was 10 now changed to 10AWG (4)Color@Color Chart1 01 :- In stibo it was Blank now Changed to White (5)Material@OuterShield1 1 - In stibo it is Tri-Laminate (Alum+Poly+Alum) But in BPCS (Checkerboard EAA+ Alum+ Poly+Alum) (6)Coverage@OuterShield1 2 - in stibo it was 95% Now changed to 94% (6)Cable Diameter (Nominal)- In Stibo it was Blank Now Changed to 0.403 in |
|--------|---|

History

| | |
|----------------------|--|
| Update and Revision: | Revision Number: 0.483 Revision Date: 05-03-2023 |
|----------------------|--|

Part Numbers

Variants

| Item # | Color | Putup Type | Length | UPC | Footnote |
|---------------|-------|------------|----------|--------------|----------|
| 7810R 010500 | Black | Reel | 500 ft | 612825189824 | C |
| 7810R 0101000 | Black | Reel | 1,000 ft | 612825189817 | C |

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.