



Product: [7927A](#)

DataTuff® Cat 6, 4 Bonded-Pr #23 Sol BC, PO Ins, PVC Jkt, Oil- and Sun-Res CMR

Request Sample

### Product Description

Industrial Ethernet Cat 6, 4 Bonded-Pair 23AWG (Solid) Bare Copper, PO Insulation, PVC Outer Jacket, Oil- and Sun-Res CMR

### Technical Specifications

#### Product Overview

Suitable Applications:	harsh environment, IIoT, factory or process automation, IP cameras and devices, data communication, etc.
Patent:	This product has one or more applicable patents. More information on patents can be found at <a href="https://www.belden.com/patents">https://www.belden.com/patents</a> .

#### Construction Details

##### Conductor

Element	Size	Stranding	Material	No. of Elements
Pair(s)	23 AWG	Solid	BC - Bare Copper	4

##### Insulation

Material	Color Code
PO - Polyolefin	White/Blue Stripe & Blue, White/Orange Stripe & Orange, White/Green Stripe & Green, White/Brown Stripe & Brown

Bonded-Pair:	Yes
--------------	-----

##### Outer Jacket

Separator	Material	Nom. Diameter	Ripcord
Center Member (Patented E-Spline®)	PVC - Polyvinyl Chloride	0.304 in (7.72 mm)	Yes

Overall Cable Diameter (Nominal):	0.304 in (7.72 mm)
-----------------------------------	--------------------

#### Electrical Characteristics

##### Electricals

Max. Conductor DCR	Max. Capacitance Unbalance
82 Ohm/km (25 Ohm/1000ft)	65.6 pF/ft

##### Delay

Max. Delay	Max. Delay Skew	Nom. Velocity of Prop.
538 ns/100m	38 ns/100m	67%

##### High Frequency

Frequency [MHz]	Max. Insertion Loss (Attenuation)	Min. NEXT [dB]	Min. PSNEXT [dB]	Min. ACR [dB]	Min. PSACR [dB]	Min. ACRF (ELFEXT) [dB]	Min. PSACRF (PSELFEXT) [dB]	Min. RL (Return Loss) [dB]	Min. SRL (Structural Return Loss) [dB]	Max./Min. Input Impedance (unFitted) [Ohm]	Max./Min. Fitted Impedance [Ohm]
1	1.9 dB/100m	82.3	80.3	80.5	78.5	73.8	70.8	20	27	100 ± 12	100 ± 15
4	3.6 dB/100m	73.3	71.3	69.7	67.7	61.8	58.8	23	27	100 ± 12	100 ± 10.4
8	5.1 dB/100m	68.8	66.8	63.7	61.7	55.7	52.7	24.5	27	100 ± 12	100 ± 8
10	5.7 dB/100m	67.3	65.3	61.6	59.6	53.8	50.8	25	27	100 ± 12	100 ± 7.3
16	7.2 dB/100m	64.3	62.3	57	55	49.7	46.7	25	27	100 ± 12	100 ± 5.7
20	8.1 dB/100m	62.8	60.8	54.7	52.7	47.8	44.8	25	27	100 ± 12	100 ± 5
25	9.1 dB/100m	61.3	59.3	52.3	50.3	45.8	42.8	25	27	100 ± 15	100 ± 5
31.25	10.2 dB/100m	59.9	57.9	49.7	47.7	43.9	40.9	25	27	100 ± 15	100 ± 5

62.5	14.7 dB/100m	55.4	53.4	40.7	38.7	37.9	34.9	25	27	100 ± 15	100 ± 5
100	18.9 dB/100m	52.3	50.3	33.4	31.4	33.8	30.8	25	27	100 ± 15	
155	23.9 dB/100m	49.5	47.5	25.5	23.5	30	27	22.8	24.7	100 ± 15	
200	27.5 dB/100m	47.8	45.8	20.3	18.3	27.8	24.8	21.7	23.4	100 ± 15	
250	31.2 dB/100m	46.3	44.3	15.2	13.2	25.8	22.8	20.5	22.2	100 ± 20	
300	34.5 dB/100m	43.2	41.2	10.6	8.6	24.3	21.3	20.2	21.2	100 ± 20	
310	35.2 dB/100m	42.9	40.9	9.8	7.8	24	21	20.1	21.1	100 ± 20	
350	37.7 dB/100m	42.2	40.2	6.5	4.5	22.9	19.9	19.8	20.4	100 ± 22	
400	40.6 dB/100m	41.3	39.3	2.6	0.6	21.8	18.8	19.5	19.7	100 ± 22	
450	43.5 dB/100m	40.5	38.5	2.1	0.1	20.7	17.7	18.9	19.1	100 ± 22	
460	44.0 dB/100m	40.4	38.4	0	0	20.5	17.5	18.8	19	100 ± 22	
500	46.2 dB/100m	39.8	37.8			19.8	16.8	18.4	18.5	100 ± 22	
550	48.8 dB/100m	39.2	37.2			19	16	18	18	100 ± 22	
600	51.4 dB/100m	38.6	36.6			18.2	15.2	17.6	17.6	100 ± 22	

#### Voltage

<b>UL Voltage Rating</b>
300 V (CMR)

### Mechanical Characteristics

#### Temperature

UL Temperature	Operating	Installation	Storage
60°C	-40°C To +75°C	-25°C To +75°C	-40°C To +75°C

#### Bend Radius

<b>Stationary Min.</b>
0.25 in (6.4 mm)

Max. Pull Tension:	45 lbs (20 kg)
Bulk Cable Weight:	38 lbs/1000ft

### Standards and Compliance

Environmental Suitability:	Riser, Indoor, Sunlight Resistance, Oil Resistance
Flammability / Reaction to Fire:	UL1666 Riser, FT4, IEC 60332-1-2
CPR Compliance:	CPR Euroclass: Eca
NEC / UL Compliance:	Article 800, CMR
CEC / C(UL) Compliance:	CMR
NEMA Compliance:	ANSI/NEMA WC-66
Data Category:	Category 6
TIA/EIA Compliance:	ANSI/TIA-568.2-D Category 6
ISO/IEC Compliance:	ISO/IEC 11801-1, IEC 61156-5
European Directive Compliance:	EU Directive 2015/863/EU (RoHS 2 amendment), REACH, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE), REACH: 2020-01-16
UK Regulation Compliance:	UKCA Mark
APAC Compliance:	China RoHS II (GB/T 26572-2011)

### Product Notes

Notes:	Third party verified to TIA/EIA-568-B.2, Category 6. Operating temperature subject to length de-rating. Cable passes -40C Cold Bend per UL 1581.
--------	--

### History

Update and Revision:	Revision Number: 0.425 Revision Date: 11-27-2023
----------------------	--

### Part Numbers

#### Variants

Item #	Color	Putup Type	Length	UPC	Footnote
7927A 0101000	Black	Reel	1,000 ft	612825191445	C
7927A 0102000	Black	Reel	2,000 ft	612825191452	C
7927A 0105000	Black	Reel	5,000 ft	612825191469	C

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.