



Product: [7965ELW](#)

Category 6 Cable, 4 Pair, U/UTP, LSZH Indoor CPR Cca

Product Description

Category 6 Premise Horizontal Cable (250MHz), 4-Pair, 23 AWG Solid Bare Copper Conductors, U/UTP, Polyethylene Insulation, LSZH Jacket CPR Cca

Technical Specifications

Product Overview

| | |
|------------------------|---|
| Suitable Applications: | Horizontal and building backbone cable; Support current and future Category 6 and 5e applications, such as: 1000Base - T (Gigabit Ethernet), 100 Base - T, 10 Base - T, FDDI, ATM |
|------------------------|---|

Construction Details

Conductor

| Size | Stranding | Material | Number of Pairs | Number of Element |
|--------|-----------|------------------|-----------------|-------------------|
| 23 AWG | Solid | BC - Bare Copper | 4 | 8 |

Insulation

| Material | Nom. Insulation Diameter | Color Code |
|-------------------|--------------------------|--|
| PE - Polyethylene | 1 mm (0.039 in) | White/Blue & Blue, White/Orange & Orange, White/Green & Green, White/Brown & Brown |

Cable Core

| Description |
|--------------------------|
| 4 pairs twisted together |

Outer Jacket

| Material | Nom. Diameter |
|---|------------------|
| LSZH - Low Smoke Zero Halogen (Flame Retardant) | 6.6 mm (0.26 in) |

Overall Cable Diameter (Nominal): 6.6 mm (0.26 in)

Electrical Characteristics

Electricals

| Max. Conductor DCR | Max. Mutual Capacitance | Max. Capacitance Unbalance | Nom. Characteristic Impedance |
|--------------------|-------------------------|----------------------------|-------------------------------|
| 95 Ohm/km | 56 pF/m (17 pF/ft) | 160 pF/100m | 100 Ohm |

Delay

| Max. Delay Skew | Nom. Velocity of Prop. |
|-----------------|------------------------|
| 40 ns/100m | 70% |

High Frequency

| Frequency [MHz] | Max. Insertion Loss (Attenuation) | Min. NEXT [dB] | Min. PSNEXT [dB] | Min. ACR [dB] | Min. PSACR [dB] | Min. ACRF (ELFEXT) [dB] | Min. PSACRF (PSELFEXT) [dB] | Min. RL (Return Loss) [dB] | Min. TCL [dB] | Min. ELCTL [dB] |
|-----------------|-----------------------------------|----------------|------------------|---------------|-----------------|-------------------------|-----------------------------|----------------------------|---------------|-----------------|
| 1 | 2.1 dB/100m | 75.3 | 72.3 | 73.2 | 70.2 | 70.0 | 67.0 | 20 | 40 | 35 |
| 4 | 3.8 dB/100m | 66.3 | 63.3 | 62.4 | 59.4 | 58.0 | 55.0 | 23 | 34 | 23 |
| 10 | 6.0 dB/100m | 60.3 | 57.3 | 54.3 | 51.3 | 50.0 | 47.0 | 25 | 30 | 15 |
| 16 | 7.6 dB/100m | 57.2 | 54.2 | 49.6 | 46.6 | 45.9 | 42.9 | 25 | 28 | 10.9 |
| 20 | 8.5 dB/100m | 55.8 | 52.8 | 47.3 | 44.3 | 44.0 | 41.0 | 25 | 27 | 9 |
| 31.2 | 10.7 dB/100m | 52.9 | 49.9 | 42.1 | 39.1 | 40.1 | 37.1 | 23.6 | 25 | 5.1 |
| 62.5 | 15.5 dB/100m | 48.4 | 45.4 | 32.9 | 29.9 | 34.1 | 31.1 | 21.5 | 22 | |

| | | | | | | | | | |
|-----|--------------|------|------|------|------|------|------|------|-----|
| 100 | 19.9 dB/100m | 45.3 | 42.3 | 25.4 | 22.4 | 30.0 | 27.0 | 20.1 | 18. |
| 155 | 25.3 dB/100m | 42.4 | 39.4 | 17.1 | 14.1 | 26.2 | 23.2 | 18.8 | 17 |
| 200 | 29.1 dB/100m | 40.8 | 37.8 | 11.6 | 8.6 | 24.0 | 21.0 | 18.0 | 16 |
| 250 | 33.0 dB/100m | 39.3 | 36.3 | 6.3 | 3.3 | 22.0 | 19.0 | 17.3 | |

| | |
|------------------|---|
| Table Notes: | Limits below 4MHz are for information only. |
| Screening Class: | Type III |

Voltage

| |
|-----------------------|
| Voltage Rating |
| 72 V DC |

Mechanical Characteristics

Temperature

| | |
|------------------|---------------------|
| Operating | Installation |
| -30°C to +60°C | 0°C To +50°C |

Bend Radius

| | |
|------------------------|--------------------------|
| Stationary Min. | Installation Min. |
| 26 mm (1.0 in) | 52 mm |

| | |
|--------------------|---------------|
| Max. Pull Tension: | 80 N (18 lbf) |
| Bulk Cable Weight: | 52 kg/km |

Standards and Compliance

| | |
|----------------------------------|--|
| Environmental Suitability: | Indoor - Euroclass Cca |
| Flammability / Reaction to Fire: | IEC 60332-1-2 |
| CPR Compliance: | CPR Euroclass: Cca-s1a,d1,a1; CPR UKCA Class: Cca-s1a,d1,a1 |
| IEEE Compliance: | PoE: IEEE 802.3bt Type 1, Type 2, Type 3, Type 4 |
| Data Category: | Category 6 |
| TIA/EIA Compliance: | ANSI/TIA 568.2-D |
| ISO/IEC Compliance: | ISO/IEC 11801-1, IEC 61034-2 - Smoke Density Min Transmittance = 80% |
| CENELEC Compliance: | EN 50173-1, Segregation class according EN50174-2 = a |
| European Halogen Free Standards: | IEC 62821-1 Halogen Free Compliance = Yes |
| European Directive Compliance: | EU CE Mark |
| UK Regulation Compliance: | UKCA Mark |

Product Notes

| | |
|--------|--|
| Notes: | Electrical values are expected performance based on cable testing and representative performance within a typical Belden system. |
|--------|--|

History

| | |
|----------------------|---|
| Update and Revision: | Revision Number: 0.81 Revision Date: 04-12-2022 |
|----------------------|---|

Part Numbers

Variants

| Item # | Color | Putup Type | Length | EAN |
|---------------|----------------|------------|--------|---------------|
| 7965ELW.00305 | Blue | Reel | 305 m | 8719605185235 |
| 7965ELW.00500 | Blue | Reel | 500 m | 8719605175359 |
| 7965ELW.01305 | Gray, RAL 7032 | Reel | 305 m | 8719605185242 |
| 7965ELW.01500 | Gray, RAL 7032 | Reel | 500 m | 8719605185259 |

© 2022 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.