



Product: <u>7G4NCY</u> ☑

MachFlex™ 350NCY, 6 C + 1 G 4 mm² Str BC, PVC Ins, TCBS, PVC Outer Jkt

## **Product Description**

MachFlex™ Control Cable 350NCY, 6 Conductors + 1 Ground 4 mm² Stranded Bare Copper, PVC Insulation, Tinned Copper Braid Shield, PVC Outer Jacket

## **Technical Specifications**

### **Product Overview**

Suitable Applications: Applicable for occasional flexing or fixed installation connecting precision control sensors, multi axis control machines, temperature controllers, control panels, machine cutting tools, auxiliary equipment, motor speed control, production machinery and many more in noisy industrial environment.

#### **Construction Details**

#### Conductor

Element	No. of Elements	Size	Stranding	Stranding Class	Material
Conductor(s)	7	4 mm²	Stranded	Class 5	BC - Bare Copper
Ground	1	4 mm²	Stranded	Class 5	BC - Bare Copper

#### Insulation

Element	Material	Color Code
Conductor(s)	PVC - Polyvinyl Chloride	Black #1, Black #2, Black #3, Black #4, Black #5, Black #6
Ground	PVC - Polyvinyl Chloride	Yellow/Green

## Outer Shield

Shield Type	Material
Braid	Tinned Copper (TC)

### Outer Jacket

PVC - Polyvinyl Chloride

Overall Cable Diameter (Nominal):

14.2 mm (0.559 in)

## **Electrical Characteristics**

### Voltage

Voltage Rating
300 / 500 V (Max. Operating Voltage)

## **Mechanical Characteristics**

# Temperature

Operating	Installation
-5°C to +70°C (Continuous movement)	40°C to +80°C (Fixed installation)

### Bend Radius

Stationary Min.	Installation Min.
213 mm (8.39 in)	85.2 mm (3.35 in)

Bulk Cable Weight: 432 kg/km (290 lbs/1000ft)

### **Standards and Compliance**

Environmental Suitability:	Indoor, Outdoor, UV Resistance, Oil Resistance - EN 50290-2-22 (TM54)
Flammability / Reaction to Fire:	IEC 60332-1-2, DIN VDE 0482-332-1-2, DIN EN 60332-1-2
European Directive Compliance:	EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2)
APAC Compliance:	China RoHS II (GB/T 26572-2011)
Other Standard Compliance(s):	VDE 0285-525-2-51, EN 50525-2-51

# **History**

Update and Revision:	Revision Number: 0.6 Revision Date: 12-20-2024

#### **Part Numbers**

#### Variants

Item #	Color	Length
7G4NCY 010100M	Black	100 m
7G4NCY 010200M	Black	200 m
7G4NCY 010300M	Black	300 m
7G4NCY 006100M	Blue	100 m
7G4NCY 006200M	Blue	200 m
7G4NCY 006300M	Blue	300 m
7G4NCY G8U100M	Gray, RAL 7001	100 m
7G4NCY G8U200M	Gray, RAL 7001	200 m
7G4NCY G8U300M	Gray, RAL 7001	300 m

### © 2025 Belden, Inc

#### All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.