

Product: <u>7X0.75</u> ☑ MachFlex™ 350YY, 7C 0.75 mm² Str BC, PVC Ins, PVC Jkt

Product Description

MachFlex™ 350YY Control VDE Certified, 7 Conductor 0.75 mm² Stranded Bare Copper, PVC Insulation, PVC Jacket

Technical Specifications

Product Overview

Product Overview					
	Applicable for occasional flexing or fixed installation connecting precision control sensors, multi axis control machines, temperature controllers, control panels, machine cutting tools, auxiliary equipment, motor speed control, production machinery and many more.				
Construction Details					
Conductor					
Element No. of Element	ts Size Stranding Stranding Class Material				
Conductor(s) 7	0.75 mm² Stranded Class 5 BC - Bare Copper				
nsulation					
Element Materia					
Conductor(s) PVC - Polyviny	I Chloride Black #1, Black #2, Black #3, Black #4, Black #5, Black #6, Black #7				
Outer Jacket					
Material					
PVC - Polyvinyl Chloride					
Overall Cable Diameter (Nominal):	7.5 mm (0.30 in)				
Electrical Characterist	tics				
Voltage					
Voltage Rating					
300/500 V (Max. Operating Vo	litage)				
Mechanical Character	istics				
Temperature					
Operating	Installation				
-15°C to +70°C(Occasional mo	ovement) -40°C to +80°C(Fixed installation)				
Bend Radius					
Installation Min. Flexing Mi	in.				
30 mm (1.2 in) 75 mm (3.0	lin)				
Bulk Cable Weight:	99 kg/km (67 lbs/1000ft)				
Standards and Compl	iance				
Environmental Suitability:	Indoor, Outdoor, Oil Resistance - EN 50290-2-22 (TM54)				
Flammability / Reaction to Fire:	IEC 60332-1-2, DIN VDE 048233212, DIN EN 6033212				
Third Party Performance Verification:	VDE Certification No. 40041970, VDE Registration No. 8770				

European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2)
APAC Compliance:	China RoHS II (GB/T 26572-2011)
Other Standard Compliance(s):	VDE 0285-525-2-51, IEC 60227-5, EN 50525-2-51

History

Update and Revision: Revision Number: 0.62 Revision Date: 03-19-2024

Part Numbers

Variants						
ltem #	Color	Length				
7X0.75 010100M	Black, RAL 9004	100 m				
7X0.75 010200M	Black, RAL 9004	200 m				
7X0.75 010300M	Black, RAL 9004	300 m				
7X0.75 G8U100M	Gray, RAL 7001	100 m				
7X0.75 G8U200M	Gray, RAL 7001	200 m				
7X0.75 G8U300M	Gray, RAL 7001	300 m				

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.